			DATE	REV	ECN	DESCRIPTION
<u>PRODUCT</u>	<u>SPECIFICATION</u>		7/6/2010	D	#13004	SPECIFICATION UPDATED
<u>Parent Number:</u> <u>Description:</u>	F18098- 18 16/30 TC AWM 3070/3231 SFF-2 SEWF-2 Braided Silicone	DIAMETER: (TOLERANCE ± : (
Stranding:	<u>16/30 TC LHL</u>			▼	м	IN AVERAGE WALL: 0.030
<u>Style:</u>	UL: AWM 3070/3231 SFF-2 CSA: SEWF-2					MINIMUM WALL: 0.027
Insulation:	Braided Silicone					
<u>Print Legend:</u>	18 AWG (0.823mm2) E22337 (PLANT ID CODE) (UL) TY	PE SFF-2 OR AWM 307	<u>0/3231 1500</u>	<u> 600V</u>	- <u>156016 CS</u>	SA SEWF-2 150C 600V FT1
<u>Voltage:</u>	<u>600V</u>					
<u>Temperature:</u>	<u>150C</u>					
<u>Notes:</u>	 Diameter shown is OD under braid. The OD over the braid is approximately 0.116". 					
The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.						
This specification is p without written conser	roprietary intellectual property of Coleman Cable. Any information on to f Coleman Cable.	contained herein shall not be	e disclosed to	any party	CO	LEMAN CABLE, INC
<u>Customer Appro</u> Customer Part	oval: t Nbr(s):				1530 Sk	nields Drive
	Date:				Phone:	can, 1L 60085 1-800-323-9355
Title:		Name:				emancable.com