



**Speaker and Control Cable**

**Multi-Conductor, Shielded, Plenum**

NEC Type CL3P (UL) and/or NEC Type CMP (UL) c(UL)

**PLENUM CABLE - PVC INSULATION, PVC JACKET**

CATALOG NUMBER	NO. OF COND.	AWG SIZE	COND. STRAND	Nom. Insulation Wall		Nom. Jacket Wall		NOMINAL O.D.		NEC TYPE
				Inches	mm	Inches	mm	Inches	mm	
<b>22 AWG CONDUCTORS</b>										
SSS222P	2	22	7/30	0.008	0.20	0.015	0.38	0.128	3.25	CL3P & CMP
SSS224P	4	22	7/30	0.008	0.20	0.015	0.38	0.147	3.73	CL3P & CMP
<b>20 AWG CONDUCTORS</b>										
SSS202P	2	20	7/28	0.008	0.20	0.015	0.38	0.139	3.53	CL3P & CMP
SSS204P	4	20	7/28	0.008	0.20	0.015	0.38	0.161	4.09	CL3P & CMP
<b>18 AWG CONDUCTORS</b>										
SSS182P	2	18	7/26	0.008	0.20	0.015	0.38	0.159	4.04	CL3P & CMP
SSS184P	4	18	7/26	0.008	0.20	0.015	0.38	0.185	4.70	CL3P & CMP
<b>16 AWG CONDUCTORS</b>										
SSS162P	2	16	19/.0117	0.008	0.20	0.015	0.38	0.179	4.55	CL3P & CMP
SSS164P	4	16	19/.0117	0.008	0.20	0.015	0.38	0.209	5.31	CL3P & CMP
<b>14 AWG CONDUCTORS</b>										
SSS142P	2	14	19/.0147	0.008	0.20	0.015	0.38	0.207	5.26	CL3P
SSS144P*	4	14	19/.0147	0.008	0.20	0.015	0.38	0.260	6.60	CL3P
<b>12 AWG CONDUCTORS</b>										
SSS122P	2	12	19/.0185	0.008	0.20	0.015	0.38	0.244	6.20	CL3P
SSS124P*	4	12	19/.0185	0.008	0.20	0.015	0.38	0.288	7.32	CL3P

**PRODUCT CONSTRUCTION**

**Conductor:**

- Stranded bare copper per ASTM B-3

**Insulation:**

- CMP - Plenum PVC

**Shield:**

- 100% Foil Shield
- Stranded Tinned Copper Drain

**Jacket:**

- CMP - Plenum PVC

**Jacket Color:**

- CMP - White (Natural)

**APPLICATIONS**

- Power-limited control circuits
- Wiring of the following systems:
  - Intercom
  - Security
  - Audio
  - Background Music

**PACKAGING**

- 500 ft. or 1000 ft. Boxes & Reels
- \*Reels only

**Color Code Chart**

NO OF. COND.	COLOR
1	Black
2	Red
3	White
4	Green

