



# Southwire®

## SPECIFICATION SHEET

**PRODUCT DESCRIPTION:** 10-105 SBC 3/C STOW 60\* PAPER 600V

**STOCK NUMBER:** 58-08-67-01

**JACKET:**

**NOMINAL OUTSIDE DIAMETER:** .675" in.  
**NOMINAL WALL THICKNESS:** .095" in.  
**COMPOUND:** Polyvinyl Chloride

**CONDUCTOR:**

**NUMBER OF CONDUCTORS:** 3  
**COLOR ROTATION:** Brown, light blue, green/yellow  
**NOMINAL OUTSIDE DIAMETER:** .216" in.  
**NOMINAL WALL THICKNESS:** .045" in.  
**INSULATION COMPOUND:** Polyvinyl Chloride  
**COPPER:** 10 AWG 105X.010" SBC

**TEMPERATURE:** 60\*

**FILLERS:** PAPERFILLER

**PRINT:**

**INDENT**

**PRINT DESCRIPTION:** (UL) VW-1 E46194 (M) STOW 3/C 10 AWG (5.26mm<sup>2</sup>) 60°C WATER RESISTANT  
600V (CSA) FT1,FT2 LL90458 (M)

**PRODUCT MANUFACTURED IN ACCORDANCE TO:**

*UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194*

*CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458*

**SOUTHWIRE COMPANY**

3800 Industrial Parkway  
MINERAL WELLS, TEXAS 76067  
TEL (940) 328-1047  
FAX (940) 328-1013