



# Southwire®

## SPECIFICATION SHEET

**PRODUCT DESCRIPTION:** STOW 10/3 105 SBC N/F

**PRODUCT CODE:** 700818

**JACKET:**

<b>NOMINAL OUTSIDE DIAMETER:</b>	.670"	in.
<b>NOMINAL WALL THICKNESS:</b>	.095"	in.
<b>COMPOUND:</b>	Polyvinyl Chloride	

**CONDUCTOR:**

<b>NUMBER OF CONDUCTORS:</b>	3	
<b>NOMINAL OUTSIDE DIAMETER:</b>	.216"	in.
<b>NOMINAL WALL THICKNESS:</b>	.045"	in.
<b>INSULATION COMPOUND:</b>	Polyvinyl Chloride	
<b>COPPER:</b>	10AWG 105X.010" SBC	

**TEMPERATURE:** 60\*

**FILLERS:** N/A

**PRINT:**

**INDENT**

(UL) VW-1 E46194 (M) STOW 3/C 10 AWG (5.26mm<sup>2</sup>) 60°C WATER RESISTANT 600V (CSA) FT1,FT LL90458 (M)

**PRODUCT MANUFACTURED IN ACCORDANCE TO:**

*UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194*

*CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458*

**SOUTHWIRE COMPANY**

3800 Industrial Parkway  
MINERAL WELLS, TEXAS 76067  
TEL (940) 328-1047

FAX (940) 328-1013

