



Southwire®

SPECIFICATION SHEET

PRODUCT DESCRIPTION: 10-105 4/C SBC STOW 60°C N/F 600V

PRODUCT CODE: 56-52-03-01

JACKET:

NOMINAL OUTSIDE DIAMETER:	.720"	in.
NOMINAL WALL THICKNESS:	.095"	in.
COMPOUND:	Polyvinyl Chloride	

CONDUCTOR:

NUMBER OF CONDUCTORS:	4	
NOMINAL OUTSIDE DIAMETER:	.216"	in.
NOMINAL WALL THICKNESS:	.045"	in.
INSULATION COMPOUND:	Polyvinyl Chloride	
COPPER:	10AWG 105X.010" SBC	

TEMPERATURE: 60*

FILLERS: N/A

PRINT:

INDENT
(UL) VW-1 E46194 (M) STOW 4/C 10 AWG (5.26mm²) 60°C WATER RESISTANT 600V
(CSA) FT1,FT2 LL90458 (M)

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194

CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458

SOUTHWIRE COMPANY

3800 Industrial Parkway
MINERAL WELLS, TEXAS 76067
TEL (940) 328-1047
FAX (940) 328-1013