



# Southwire®

## SPECIFICATION SHEET

**PRODUCT DESCRIPTION:** 12-65 4/C TIN CU STOOW Paper 105\* 600V

**PRODUCT CODE:** 56-47-43-01

**JACKET:**

**NOMINAL OUTSIDE DIAMETER:** .665" in.  
**NOMINAL WALL THICKNESS:** .095" in.  
**COMPOUND:** Polyvinyl Chloride

**CONDUCTOR:**

**NUMBER OF CONDUCTORS:** 4  
**NOMINAL OUTSIDE DIAMETER:** .190" in.  
**NOMINAL WALL THICKNESS:** .045" in.  
**COPPER:** 12AWG 65X.010" STC

**TEMPERATURE:** 105°C

**FILLERS:** Paperfiller

**PRINT:** **INK**  
(UL) VW-1 E46194 (M) STOOW 4/C 12 AWG (3.31mm<sup>2</sup>) 105°C DRY 60°C WATER RESISTANT  
600V (CSA) FT1,FT2 LL90458 (M)

**PRODUCT MANUFACTURED IN ACCORDANCE TO:**

*UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194*  
*CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458*

**SOUTHWIRE COMPANY**

3800 Industrial Parkway  
MINERAL WELLS, TEXAS 76067  
TEL (940) 328-1047  
FAX (940) 328-1013