

NOMA CABLETECH SPECIFICATION SHEET

PRODUCT CODE: 701952

PRODUCT DESCRIPTION: STW 14/3 41 SBC 105* N/F

JACKET:

NOMINAL OUTSIDE DIAMETER:	.530"	in.
NOMINAL WALL THICKNESS:	.080"	in.
COMPOUND:	Polyvinyl Chloride	

CONDUCTOR:

NUMBER OF CONDUCTORS:	3	
NOMINAL OUTSIDE DIAMETER:	.168"	in.
NOMINAL WALL THICKNESS:	.045"	in.
INSULATION COMPOUND:	Polyvinyl Chloride	
COPPER:	14 AWG 41X.010" SBC	

TEMPERATURE: 105*

FILLERS: N/A

PRINT:

PRINT DESCRIPTION: **INK**
UL VW-1 E47523 M STW 14/3 600V 105°C DRY 60°C WATER RESISTANT CSA FT1 FT2
LL26332 M

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - NOMA CABLETECH FILE NO. E47523
CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - NOMA CABLETECH FILE NO. LL26332

NOMA CABLE TECH

PO BOX 730
MINERAL WELLS, TEXAS 76068
TEL (940) 328-1047
FAX (940) 328-1013