



Southwire®

SPECIFICATION SHEET

PRODUCT DESCRIPTION: 16-26 3/C CU STOW N/F 105* 600V

PRODUCT CODE: 56-47-46-01

JACKET:

NOMINAL OUTSIDE DIAMETER: .390" in.
NOMINAL WALL THICKNESS: .060" in.
COMPOUND: Polyvinyl Chloride

CONDUCTOR:

NUMBER OF CONDUCTORS: 3
NOMINAL OUTSIDE DIAMETER: .120" in.
NOMINAL WALL THICKNESS: .030" in.
COPPER: 16AWG 26X.010" SBC

TEMPERATURE: 105°C

FILLERS: N/F

PRINT: **INDENT**
(UL) VW-1 E46194 (M) STOW 3/C 16 AWG (1.31mm²) 105°C DRY 60°C WATER RESISTANT
600V (CSA) FT1,FT2 LL90458 (M)

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194

CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458

SOUTHWIRE COMPANY

3800 Industrial Parkway
MINERAL WELLS, TEXAS 76067
TEL (940) 328-1047
FAX (940) 328-1013