

TYPE SE-SEO-SEOW•UL•CSA•600V•105°C*

Supplied on a 30" Non Returnable Reel

| CONDUCTOR NO. | CONDUCTOR | | | NOMINALS (INCHES) | | | AMPS | SHIP WT. LBS./M FT. |
|---------------|-----------|--------|--|-------------------|--------|------|------|---------------------|
| | AWG. | STRD | | INSUL | JACKET | O.D. | | |
| 2 | 18 | 16x30 | | .030 | .060 | .345 | 10 | 65 |
| 3 | 18 | 16x30 | | .030 | .060 | .361 | 10 | 76 |
| 4 | 18 | 16x30 | | .030 | .060 | .390 | 7 | 89 |
| 2 | 16 | 26x30 | | .030 | .060 | .369 | 13 | 76 |
| 3 | 16 | 26x30 | | .030 | .060 | .387 | 13 | 91 |
| 4 | 16 | 26x30 | | .030 | .060 | .419 | 10 | 103 |
| 2 | 14 | 41x30 | | .045 | .080 | .501 | 18 | 127 |
| 3 | 14 | 41x30 | | .045 | .080 | .526 | 18 | 152 |
| 4 | 14 | 41x30 | | .045 | .080 | .569 | 15 | 186 |
| 2 | 12 | 65x30 | | .045 | .095 | .573 | 25 | 167 |
| 3 | 12 | 65x30 | | .045 | .095 | .601 | 25 | 208 |
| 2 | 10 | 105x30 | | .045 | .095 | .630 | 30 | 230 |
| 3 | 10 | 105x30 | | .045 | .095 | .670 | 30 | 280 |

Conductor: Fully annealed stranded bare copper.

Insulation/Jacket: Thermoplastic (PVC) or Elastomer

Temperature: 105°C or 60°C (221°F or 140°F) to -50°C

Note: Available with green or green/yellow ground.

Application: For use as portable power cord for power tools, motors, appliances and hospital equipment. Excellent resistance to water, acids, ozone and oils.

Listed: UL-62 CSA C22.2-49 OSHA RoHS Compliant

TYPE ST-STO-STOW•UL•CSA•600V•60°C-105°C*

Supplied on a 30" Non Returnable Reel

| CONDUCTOR NO. | CONDUCTOR | | | NOMINALS (INCHES) | | | AMPS | SHIP WT. LBS./M FT. |
|---------------|-----------|--------|--|-------------------|--------|------|------|---------------------|
| | AWG. | STRD | | INSUL | JACKET | O.D. | | |
| 2 | 18 | 16x30 | | .030 | .060 | .345 | 10 | 65 |
| 3 | 18 | 16x30 | | .030 | .060 | .361 | 10 | 76 |
| 4 | 18 | 16x30 | | .030 | .060 | .390 | 7 | 89 |
| 2 | 16 | 26x30 | | .030 | .060 | .369 | 13 | 76 |
| 3 | 16 | 26x30 | | .030 | .060 | .387 | 13 | 91 |
| 4 | 16 | 26x30 | | .030 | .060 | .419 | 10 | 103 |
| 2 | 14 | 41x30 | | .045 | .080 | .501 | 18 | 127 |
| 3 | 14 | 41x30 | | .045 | .080 | .526 | 18 | 152 |
| 4 | 14 | 41x30 | | .045 | .080 | .569 | 15 | 186 |
| 2 | 12 | 65x30 | | .045 | .095 | .573 | 25 | 167 |
| 3 | 12 | 65x30 | | .045 | .095 | .601 | 25 | 208 |
| 2 | 10 | 105x30 | | .045 | .095 | .630 | 30 | 230 |
| 3 | 10 | 105x30 | | .045 | .095 | .670 | 30 | 280 |

Conductor: Fully annealed stranded bare copper

Insulation/Jacket: Thermoplastic (PVC) 600 volt

Temperature: 105°C or 60°C (221°F or 140°F) to -40°C

Note: Available with green or green/yellow ground.

Applications: For use as portable power cord for power tools, motors, appliances and hospital equipment. Excellent resistance to water, acids, ozone and oils.

Listed: UL-62 CSA C22.2-49 OSHA RoHS Compliant

*Please contact U.S. Wire & Cable for availability.

