

TYPE SE-SEO-SEOW•UL•CSA•600V•105°C*

Supplied on a 30" Non Returnable Reel

CONDUCTOR NO.	CONDUCTOR			NOMINALS (INCHES)			AMPS	SHIP WT. LBS./M FT.
	AWG.	STRD		INSUL	JACKET	O.D.		
2	18	16x30		.030	.060	.345	10	65
3	18	16x30		.030	.060	.361	10	76
4	18	16x30		.030	.060	.390	7	89
2	16	26x30		.030	.060	.369	13	76
3	16	26x30		.030	.060	.387	13	91
4	16	26x30		.030	.060	.419	10	103
2	14	41x30		.045	.080	.501	18	127
3	14	41x30		.045	.080	.526	18	152
4	14	41x30		.045	.080	.569	15	186
2	12	65x30		.045	.095	.573	25	167
3	12	65x30		.045	.095	.601	25	208
2	10	105x30		.045	.095	.630	30	230
3	10	105x30		.045	.095	.670	30	280

Conductor: Fully annealed stranded bare copper.

Insulation/Jacket: Thermoplastic (PVC) or Elastomer

Temperature: 105°C or 60°C (221°F or 140°F) to -50°C

Note: Available with green or green/yellow ground.

Application: For use as portable power cord for power tools, motors, appliances and hospital equipment. Excellent resistance to water, acids, ozone and oils.

Listed: UL-62 CSA C22.2-49 OSHA RoHS Compliant

TYPE ST-STO-STOW•UL•CSA•600V•60°C-105°C*

Supplied on a 30" Non Returnable Reel

CONDUCTOR NO.	CONDUCTOR			NOMINALS (INCHES)			AMPS	SHIP WT. LBS./M FT.
	AWG.	STRD		INSUL	JACKET	O.D.		
2	18	16x30		.030	.060	.345	10	65
3	18	16x30		.030	.060	.361	10	76
4	18	16x30		.030	.060	.390	7	89
2	16	26x30		.030	.060	.369	13	76
3	16	26x30		.030	.060	.387	13	91
4	16	26x30		.030	.060	.419	10	103
2	14	41x30		.045	.080	.501	18	127
3	14	41x30		.045	.080	.526	18	152
4	14	41x30		.045	.080	.569	15	186
2	12	65x30		.045	.095	.573	25	167
3	12	65x30		.045	.095	.601	25	208
2	10	105x30		.045	.095	.630	30	230
3	10	105x30		.045	.095	.670	30	280

Conductor: Fully annealed stranded bare copper

Insulation/Jacket: Thermoplastic (PVC) 600 volt

Temperature: 105°C or 60°C (221°F or 140°F) to -40°C

Note: Available with green or green/yellow ground.

Applications: For use as portable power cord for power tools, motors, appliances and hospital equipment. Excellent resistance to water, acids, ozone and oils.

Listed: UL-62 CSA C22.2-49 OSHA RoHS Compliant

*Please contact U.S. Wire & Cable for availability.

