

FOR REFERENCE ONLY, THIS IS NOT A CONTROLLED DOCUMENT

PRODUCT SPECIFICATION

May 1, 2008

PART NUMBER: 2216144

DESCRIPTION: STW 16(26B)/4 105C POLY-P WHITE
.430",CC099(RED-BLK-WHT-LGRN),SMOOTH,INDENT IW020,
FT1,UL/CSA
30" PLY REEL-NR,899M(2950FT)

CONDUCTOR: Stranded #16 awg 26x.0100" soft bare copper

#16 INSULATION: Lead Free PVC .030" nominal thickness
DIAMETER: .121" +/- .002"

ASSEMBLY: Cabled with poly fillers and a 2.625" +/- .125" lay.
Paper separator applied between core and jacket.

COLOUR SEQUENCE: Black-White-Light Green-Red (clockwise at top of spool)

JACKET: Lead Free PVC .060" nominal thickness.
DIAMETER: .430" +/- .008"

PRINT TYPE: INDENT

PRINT LEGEND: CSA LL39965 STW 4/C 1,31mm² (16 AWG) 105°C DRY, 60°C WATER RESISTANT
600V FT1 (UL) E67474

TEMPERATURE: -40°C to 105°C

VOLTAGE: 600

FLAME RATING: FT1

REGULATORY

APPROVALS: CSA FILE NUMBER LL39965
UL FILE NUMBER E67474