KALAS
Commitment Backed by Capability
25 Main Street · P.O. Box 328 · Denver, PA 17517
Main (717) 336–5575 · Dir. (717) 335-0128 · Fax (717) 335-1918

Proposed Specification Sheet

Part Number: SR09011 **Revision:** 00 **Date:** October 6, 2009
Description: STOOW 16/5 26B VW-1 105C * ROHS COMPLIANT

Conductor:	Gauge:	16		
	Strand Qty:	26		
	Strand diameter:	0.0100		
	Type:	Bare Copper		
Insulation:	Type:	PVC		
	Color/Sequence:	Black/Orange/Green/Red/White		
	Wall:	0.030"		
	Diameter:	0.123"	Tolerance +	0.003"
			Tolerance -	0.003"
Filler:		Poly		
Separator:		Paper		
Jacketing:	Type:	PVC		
	Color:	Yellow		
	Wall:	0.080"		
	Diameter:	0.505"	Tolerance +	0.010"
			Tolerance -	0.010"
Approvals:		UL, CSA		
RoHS compliant European Directive 2002/95/EC:		Yes		
Print Legend:		5/C 16 AWG (^1.31mm2^) E31793 (UL) STOOW 600V 105°C (WATER RESISTANT 60°C) VW-1 --- 5/C 1.31mm2 (^16 AWG^) LL22035 CSA STOOW 600V 105°C FT1 FT2 --- RoHS COMPLIANT **PLUS DD/MM/YYYY**		
Max Voltage Rating:		600 volts		
Product weight:		142.0 lb./1000'		
Packaging:		1,000' on 24X12X8" Reel		

Created/revised by: _____ **10/06/2009**
sign/date

Checked by: TLR **10/06/2009**
sign/date