

YR40916
MCGRAW-EDISON P/N KA6012-4

I. DESCRIPTION:

12 CONDUCTOR #16 AWG SHIELDED PORTABLE CORDAGE.

II. RECOGNIZED BY:

UL AND CSA

III. COLOR CODING:

GREEN, ORANGE, BLUE, WHITE/BLACK, RED/BLACK, GREEN/BLACK,
ORANGE/BLACK, BLUE/BLACK, BLACK/WHITE @ BLACK, WHITE, RED

IV. ELECTRICAL CHARACTERISTICS:

VOLTAGE RATING: 600 V RMS
DIELECTRIC WITHSTAND: 1500 V AC APPLIED FOR
1 MIN.

V. PHYSICAL CHARACTERISTICS:

TYPE OF CORDAGE: AWM 2501
C(UR) FOR USE IN CANADA*

NO. OF CONDUCTORS: 12
AWG SIZE: 16
STRANDING: (65X34) TINNED
INSULATION: .0325" WALL TPE
SEPARATOR UNDER BRAID: .001" THICK POLYESTER
TYPE SHIELD & % COVERAGE: T.C. BRAID; 90%
SEPARATOR OVER BRAID: .003" THICK PAPER
JACKET: .075" WALL BELFLEX
DIAMETER: .712" +/- .020"
TEMPERATURE RATING: 105 C

*C(UR) IS THE UL SYMBOL THAT CABLE MEETS CSA AWM STANDARDS.