



## SPECIFICATION SHEET

**PRODUCT DESCRIPTION:** STW 18/3 16SBC 105\* N/F

**PRODUCT CODE:** 701428

**JACKET:**

**NOMINAL OUTSIDE DIAMETER:** .363" in.  
**NOMINAL WALL THICKNESS:** .060" in.  
**COMPOUND:** Polyvinyl Chloride

**CONDUCTOR:**

**NUMBER OF CONDUCTORS:** 3  
**NOMINAL OUTSIDE DIAMETER:** .109" in.  
**NOMINAL WALL THICKNESS:** .030" in.  
**INSULATION COMPOUND:** Polyvinyl Chloride  
**COPPER:** 18 AWG 16X010 SBC

**TEMPERATURE:** 105\*

**FILLERS:** N/A

**PRINT:** INK

**PRINT DESCRIPTION:** (UL) VW-1 E47523 (M) STW 18/3 105°C DRY 60°C WATER RESISTANT  
(CSA) FT1,FT2 LL26332 (M)

**PRODUCT MANUFACTURED IN ACCORDANCE TO:**

*UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - CABLETECH FILE NO. E47523*  
*CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - CABLETECH FILE NO. LL26332*

**CABLE TECH GLOBAL**

3800 Industrial Parkway  
MINERAL WELLS, TEXAS 76067  
TEL (940) 328-1047  
FAX (940) 328-1013