



Southwire®

SPECIFICATION SHEET

PRODUCT DESCRIPTION: 18-41 3/C CU SVT 105* Paper

PRODUCT CODE: 56-46-50-01

JACKET:

NOMINAL OUTSIDE DIAMETER: .255" in.
NOMINAL WALL THICKNESS: .030" in.
COMPOUND: Polyvinyl Chloride

CONDUCTOR:

NUMBER OF CONDUCTORS: 3
NOMINAL OUTSIDE DIAMETER: .079" in.
NOMINAL WALL THICKNESS: .015" in.
COPPER: 18 AWG 41X.0063" SBC

TEMPERATURE: 105°C

FILLERS: Paperfiller

PRINT: **INDENT**
(UL) VW-1 E46194 (M) SVT 3/C 18 AWG (0.824mm²) 105°C 300V (CSA) FT1,FT2 LL90458 (M)

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194

CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458

SOUTHWIRE COMPANY

3800 Industrial Parkway
MINERAL WELLS, TEXAS 76067
TEL (940) 328-1047
FAX (940) 328-1013