

Domtech

Electrical Wire and Cable

Domtech Inc.
40 East Davis Street,
Trenton, Ontario
Canada K8V 6S4

Tel. (613) 394-4884
Tel. 1-800 278-8258
Fax (613) 394-0108

FOR REFERENCE ONLY, THIS IS NOT A CONTROLLED DOCUMENT

PRODUCT SPECIFICATION

September 12, 2007

PART NUMBER: 1018337

DESCRIPTION: SVT 18(41B)/3 105C NF-LT/P BLACK
.245",CC099(BLK-WHT-LGRN),RIBBED,INDENT IW011,VW-1
UL/CSA
30" PLY REEL-NR,2743M(9000FT)

CONDUCTORS: Stranded #18 awg 41 x .0063" soft bare copper

INSULATION: Lead Free PVC .015" minimum average thickness,
.079" +/- .002" diameter

ASSEMBLY: Cabled without fillers, and 1.625" +/- .125" lay
Paper separator and light talc applied between core and jacket.

COLOUR SEQUENCE: Black-White-Light Green (clockwise at top of reel).

JACKET: Lead Free PVC .030" minimum average thickness

DIAMETER: .245" +/- .005"

PRINT TYPE: Indent

PRINT LEGEND: CSA LL39965 SVT 3/C 0,824mm² (18 AWG) 105°C 300V VW-1 (UL) E67474

TEMPERATURE: -20°C to 105°C

VOLTAGE: 300

FLAME RATING: VW-1

REGULATORY

APPROVALS: CSA FILE # LL39965
UL FILE # E67474