

Domtech

Electrical Wire and Cable

Domtech Inc.
40 East Davis Street,
Trenton, Ontario
Canada K8V 6S4

Tel. (613) 394-4884
Tel. 1-800 278-8258
Fax (613) 394-0108

FOR REFERENCE ONLY, THIS IS NOT A CONTROLLED DOCUMENT

PRODUCT SPECIFICATION

June 13, 2011

PART NUMBER: 1018TBA

DESCRIPTION: SVT 18(41B)/3 105C POLY-P WHITE
.245",CC099(BLK-WHT-LGRN),SMOOTH,INDENT IW011,VW-1,UL/CSA
24" PLY REEL-NR,1524M(5000FT)

CONDUCTORS: Stranded #18 awg 41 x .0063" soft bare copper

INSULATION: Lead Free PVC .015" minimum average thickness
DIAMETER: .079" +/- .002"

ASSEMBLY: Cabled with poly fillers, and 1.625" +/- .125" lay
Paper separator applied between core and jacket

COLOUR SEQUENCE: Light Green-White-Black (clockwise at top of spool)

JACKET: Lead Free PVC .030" minimum average thickness
DIAMETER: .245" +/- .005"

PRINT TYPE: Indent

PRINT LEGEND: CSA LL39965 SVT 3/C 0,824mm² (18 AWG) 105°C 300V VW-1 (UL) E67474

TEMPERATURE: -20°C to 105°C

VOLTAGE: 300

FLAME RATING: VW-1

REGULATORY

APPROVALS: CSA FILE # LL39965
UL FILE # E67474