



Domtech Inc.
40 East Davis Street
Trenton, Ontario
Canada, K8V 6S4
Ph: 613-394-4884
Fax: 613-394-5372
Toll Free: 888-278-8258 (USA & Canada)
www.domtech.net

FOR REFERENCE ONLY, THIS IS NOT A CONTROLLED DOCUMENT

PRODUCT SPECIFICATION

February 15, 2017

PART NUMBER: 3818461

DESCRIPTION: AWM 18(41B)/4 105C NF-LT/P 300V BLACK
.270",CC047(WHT-BLK-GRN/YEL/YEL-RED),SMOOTH,INDENT IW889,
AWM 2450,VW-1/FT1,UL/CSA
30" PLY REEL-NR,2378M(7800FT)

CONDUCTOR: Stranded #18 awg 41x.0063" soft bare copper

INSULATION: PVC .015" minimum average thickness, .079" +/- .002" diameter

ASSEMBLY: Cabled without fillers and a 3.875" +/- .125" lay
Light talc and paper separator and applied between jacket and cabled assembly.

COLOUR

SEQUENCE: White - Black - Green/Yellow - Red (clockwise at top of reel)

NOTE: Colour following "/" denotes stripe colour. Each of the two yellow stripes on the green conductor is 15 to 20% coverage for a total of 30 to 40% overall.

JACKET: PVC .032" minimum average thickness


DIAMETER: .270" +/- .005"

TEMPERATURE: 105°C

FLAME RATING: VW-1/FT1

VOLTAGE RATING: 300V

PRINT TYPE: Indent

PRINT LEGEND: CSA AWM I/II A/B 300V 105C FT1 LL39965  AWM 2450 300V 105C
VW-1 E76241

SPECIFICATIONS: CSA C22.2 No 210,
UL 758 - Style 2450 (SVT type)
RoHS Compliant

APPROVALS: CSA F ile # L39965
UL File #E76241