

DATE	REV	ECN	DESCRIPTION
9/14/2015	F		Updated low temp info.


**PRODUCT SPECIFICATION**

**Parent Number:** F16032-

**Description:** 16 26/30 TC MTW or BC-5W2 or AWM  
1011/1015/1230/1335 or 1032 TEW or AWM I  
A/B

**DIAMETER:** 0.117

**TOLERANCE ± :** 0.003



**MIN AVG WALL:** 0.030

**MINIMUM WALL:** 0.027

**Stranding:** 26/30 TC LHL

**Style:** UL: MTW or BC-5W2 or AWM 1011/1015/1230/1335 or 1032  
CSA: TEW or AWM I A/B

**Insulation:** PVC

**Print Legend:** 16 AWG (1.31mm<sup>2</sup>) E69567 (PLANT ID CODE) (UL) BC-5W2 OR MTW FLEXING OR AWM 1011/1015/1230/1335 600V OR 1032 1000V  
MOISTURE RESISTANT VW-1 -- 156205 CSA TEW 105C 600V FT1 OR AWM I A/B 105C 600V FT1

**Voltage:** 600V, 1032=1000V

**Temperature:** 1011=80C, 1015=105C, 1032=90C, 1230: DRY=105C WET=60C, MTW/1335: DRY=90C WET=60C, BC-5W2: DRY=105C  
WET=75C, TEW/AWM I A/B=105C

- Notes:**
1. Min Temp: -40C
  2. CSA TEW: -30C

This product complies with European Directive 2011/65/EU (RoHS 2)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

**Customer Approval:**

**Customer Part Nbr(s):** \_\_\_\_\_

**Approved By:** \_\_\_\_\_ **Date:** \_\_\_\_\_

**Title:** \_\_\_\_\_ **Company Name:** \_\_\_\_\_



**Copperfield®**

1115 W. North Street  
Bremen, IN 46506  
Phone: 1-574-546-5115

