## **DESCRIPTION** DATE REV **ECN** 10/25/2018 Α NEW FORMAT

## **PRODUCT SPECIFICATION**

41101-Parent Number:

> **DIAMETER:** 0.106 Description: 18 16/30 BC MTW or AWM

1011/1015/1230/1335/1345 or 1032 or TEW or TOLERANCE ±: 0.003

AWM I A/B

Stranding: 16/30 BC LHL

<u>Style:</u> <u>UL: MTW or AWM 1011/1015/1230/1335/1345 or 1032 CSA:</u> TEW or AWM I A/B

Insulation: PVC

<u>Print Legend:</u> 18 AWG (0.823mm2) E51583 (PLANT ID CODE) (UL) MTW OR AWM 1011/1015/1230/1335/1345 600V OR 1032 1000V MOISTURE RESISTANT VW-1 -- 156205 CSA TEW 105C 600V FT1 OR AWM I A/B 105C 600V FT1

Voltage: 600V, 1032=1000V

Temperature: 1011=80C, 1015=105C, 1032=90C, 1230: DRY=105C WET=60C, MTW/1335: DRY=90C WET=60C, 1345: DRY=105C WET=75C,

TEW/AWM I A/B=105C

Notes: 1. Min Temp: -40C

2. CSA TEW: -30C


This product complies with European Directive 2015/863 -- RoHS 3.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer	Approval	:

Customer Part Nbr(s):		
Approved By:	Date:	
Title:	Company Name:	



*MIN AVG WALL:* 0.030

MINIMUM WALL: 0.027



Bremen, IN 46506 Phone: 1-574-546-5115