

THERM-O-LINK INC.

10513 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: IEWC

TOL Part Number: SXL-18-1016
Customer Part Number : SXL 18T-1-SP

Description: 18 GA SXL XLPE 125 DEG C 16 STRANDS TINNED
COPPER

Conductor (Stranding): 16 x .0098" Tinned Copper
Conductor OD (Nom) 0.047 inches
Max. Lay Length: .625 inch Lay
Nom. Wall Thickness: 0.030 inches
Max. O.D : 0.118 inches
Min . O.D : 0.090 inches
Max Runout : 0.008 inches
Strip Force : 5 lbs (Min) -12 lbs (Max)
Circular Mils (CMA): 1537 (Min)
Surface Print: None

Specification Reference Data

SAE: J-1128	Ford: N/A	Chrysler: N/A	
UL : N/A	CSA: N/A	Packard: N/A	Other: N/A

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Verified By: Mir Hussain (Corporate Quality Engineer)

Date: 6-26-2012
Mat'l Spec Form (#F-0270)

Rev. 0

7-30-1998