


# PRODUCT SPECIFICATION

<i>DATE</i>	<i>REV</i>	<i>ECN</i>	<i>DESCRIPTION</i>
5/21/2008	A	650-08	SPECIFICATION CREATED

**Parent Number:** F18481-

**Description:** 18 16/30 TPCT SXL per J1128

**DIAMETER:** 0.102  
**TOLERANCE ± :** 0.003



**Stranding:** 16/30 Topcoat

**Style:** SXL per SAE J1128

**Insulation:** XLPE

**Print Legend:** NO PRINT

**Voltage:** Per SAE J 1128 this product is intended for use at a nominal system voltage of 60 Volts DC or less in surface vehicle electrical systems.

**Temperature:** The Temperature Class Rating is 125C. The Temperature Class rating is defined by SAE as " a class designation based on the retention of mechanical properties after 168 hours of aging at 30C above the temperature class rating".

**Notes:**

This product complies with European Directive 2002/95/EC (RoHS)

**Customer Approval:**

**Customer Part Nbr(s):** \_\_\_\_\_

**Approved By:** \_\_\_\_\_ **Date:** \_\_\_\_\_

**Title:** \_\_\_\_\_ **Company Name:** \_\_\_\_\_

**COLEMAN CABLE, INC**

1530 Shields Drive  
Waukegan, IL 60085



Phone: 1-800-323-9355

www.colemancable.com