



# PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive  
 Waukegan, IL 60085  
 Toll-Free (800) 323-9355  
 Fax: (847) 689-1192

**PART NUMBER:** 96263  
**DESCRIPTION:** 24 AWG /4 Pair Category 5e CMR  
**COMPLIANCE:**

- ETL Listed Type CMR
- C(ETL) listed CMR FT4
- ETL Verified to TIA/EIA 568-C.2
- Tested to 350 MHz

## Construction Parameters:

Conductor	24 AWG Solid Bare Copper	<u>DIAMETER*</u>
Dielectric	Solid PE	0.020"
Assembly	Each pair has different lay length for cross-talk prevention and ripcord added.	0.036"
Jacket	PVC	0.200"

\* = Nominal value

## Product Electrical Characteristics:

Max Capacitance (nF/100m @ 1 kHz)	Max DC Resistance (Ω/100m @ 20°C)	Max Delay Skew (ns/100m)	Nom Velocity of Propagation (%)	Characteristic Impedance (Ω @ 1-100 MHz)
5.6	9.38	45	68	100 +/- 15

Freq (MHz)	Max Insertion Loss (dB/100m)	Min NEXT Loss (dB)	Min PSNEXT Loss (dB)	Min ACR (dB/100m)	Min PSACR (dB/100m)	Min ACRF (dB/100m)	Min PSACRF (dB/100m)	Min Return Loss (dB)
1	2.0	65.3	62.3	63.3	60.3	63.8	60.8	20
10	6.5	50.3	47.3	43.8	40.8	43.8	40.8	25
16	8.2	47.3	44.3	39.1	36.1	39.7	36.7	25
20	9.3	45.8	42.8	36.5	33.5	37.7	34.7	25
31.25	11.7	42.9	39.9	31.2	28.2	33.9	30.9	23.6
62.5	17.0	38.4	35.4	21.4	18.4	27.8	24.8	21.5
100	22.0	35.3	32.3	13.3	10.3	23.8	20.8	20.1
155	28.1	32.4	29.4	4.3	1.3	20.0	17.0	18.8
200	32.4	30.8	27.8	-	-	17.8	14.8	18.0
250	36.9	29.3	26.3	-	-	15.8	12.8	17.3
350	44.9	27.1	24.1	-	-	12.9	9.9	16.3

\* Note that values above 100 MHz are not guaranteed and are for engineering reference only.

Pair Colors: W/BL with BL, W/OR with O, W/GR with GR, W/BR with BR  
 Jacket Color: Standard colors are White, Yellow, Orange, Green, Blue, Gray, Pink and Black

Legend (Ink Print) SOUTHWIRE® SIGNAL® 96263 24 AWG 4PR UTP CAT5E E118871 (PLANT ID CODE) C(UL)US LISTED CMR SUN RES -- TYPE CMR FT-4 TESTED TO 350 MHZ ETL VERIFIED TO TIA/EIA-568-B.2 CAT 5E -- XX/XX/XX (MONTH/DAY/YEAR) HH:MM (HOUR/MINUTE) SEQUENTIAL FOOTAGE

(Also printed with sequential footage)

This product complies with European Directive 2011/65/EU (RoHS-2)  
 On special orders, the customer will accept all mil lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire. Any information contained herein shall not be disclosed to any party without written consent of Southwire.

Specification Issue Date: October 13, 2015