



# Southwire®

## SPECIFICATION SHEET

**PRODUCT DESCRIPTION:** 12-65 3/C CU SJTOW PAPER 105°C 300V

**PRODUCT CODE:** 56-47-01-01

**JACKET:**

<b>NOMINAL OUTSIDE DIAMETER:</b>	.445"	in.
<b>NOMINAL WALL THICKNESS:</b>	.045"	in.
<b>COMPOUND:</b>	Polyvinyl Chloride	

**CONDUCTOR:**

<b>NUMBER OF CONDUCTORS:</b>	3	
<b>NOMINAL OUTSIDE DIAMETER:</b>	.160"	in.
<b>NOMINAL WALL THICKNESS:</b>	.030"	in.
<b>INSULATION COMPOUND:</b>	Polyvinyl Chloride	
<b>COPPER:</b>	12 AWG 65X.010" SBC	

**TEMPERATURE:** 105\*

**FILLERS:** Paper filled

**PRINT:**

**INDENT**

(UL) VW-1 E46194 (M) SJTOW 3/C 12 AWG (3.31mm<sup>2</sup>) 105°C DRY 60°C WATER RESISTANT  
300V (CSA) FT1,FT2 LL90458 (M)

**PRODUCT MANUFACTURED IN ACCORDANCE TO:**

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - SOUTHWIRE FILE NO. E46194

CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - SOUTHWIRE FILE NO. LL90458

**SOUTHWIRE COMPANY**

3800 Industrial Parkway  
MINERAL WELLS, TEXAS 76067  
TEL (940) 328-1047  
FAX (940) 328-1013