

Alumaflex™ Type MC XHHW-2



6 AWG through 900 kcmil Alumaflex™ XHHW-2 Insulated Singles with 8000 series Triple E™ Aluminum Alloy. Bare Alumaflex™ Aluminum Alloy Grounding Conductor. UL Listed. 600 Volts. Lightweight Aluminum Interlocked Armor.

APPLICATIONS

Suitable for use as follows:

- Branch, feeder and service power distribution under high ambient temperatures in commercial, industrial, institutional, and multi-residential buildings.
- Power, lighting, control, and signal circuits.
- Fished or embedded in plaster.
- Concealed or exposed installations.
- Environmental air-handling spaces per NEC 300.22 (C).
- Places of Assembly per NEC 518.4 and theaters per NEC 520.5.
- Installation in cable tray and approved raceways.
- Under raised floors for information technology equipment conductors and cables per NEC 645.5(D) & 645.5(D)(2).
- Class I Div. 2, Class II Div 2, & Class III Div. 1 Hazardous Locations.

STANDARDS & REFERENCES

Southwire Alumaflex™ Type MC-XHHW-2 Cable meets or exceeds the requirements:

- UL 44
- UL 1569
- UL Online Product Guide Info - Metal-Clad Cable (PJAZ) (www.ul.com)
- ICEA S-95-658 (NEMA WC70)
- Federal Specification A-A59544 (formerly J-C-30B)
- IEEE 1202 (70,000 Btu/hr) Vertical Cable Tray Flame Test
- NFPA 70 (National Electrical Code), Article 330
- Listed for use in UL 1, 2, and 3 Hour Through-Penetration Firestop Systems
- REACH/RoHS-2 (Chemical Limit) Compliant

CONSTRUCTION

Southwire Alumaflex™ Type MC-XHHW-2 Cable with Triple E™ Aluminum Alloy is constructed with Type XHHW-2 conductors rated 90° C dry, and a bare equipment grounding conductor. Conductors are Alumaflex™ AA-8000 series aluminum alloy compact stranded. A binder tape is wrapped over the conductors. Aluminum interlocking armor is applied over the assembly. Refer to color chart for conductor color sequence.



The Power of Connections.™



Southwire®

AlumaFlex™ Type MC - Aluminum Conductors

CONDUCTOR SIZE AND COLORS	GROUNDING SIZE AND COLOR	STOCK NUMBER	WEIGHT (LBS/1000')	OVERALL DIAMETER (INCHES)
SOLID CONDUCTOR COLORS 120/208V				
6-3 STRANDED XHHW (BLACK/BLACK-WHITE/BLACK-RED)	6 STRANDED (BARE)	89-00-92-99	228	.784
6-4 STRANDED XHHW (BLACK/BLACK-BLUE/ BLACK-WHITE/BLACK-RED)	6 STRANDED (BARE)	61-12-03-99	275	.85
4-3 STRANDED XHHW (BLACK/BLACK-WHITE/BLACK-RED)	6 STRANDED (BARE)	60-07-42-99	302	.956
4-4 STRANDED XHHW (BLACK/BLACK-BLUE/ BLACK-WHITE/BLACK-RED)	6 STRANDED (BARE)	60-83-64-99	356	.949
2-3 STRANDED XHHW (BLACK/BLACK-WHITE/BLACK-RED)	4 STRANDED (BARE)	55-71-99-99	418	1.089
2-4 STRANDED XHHW (BLACK/BLACK-BLUE/ BLACK-WHITE/BLACK-RED)	4 STRANDED (BARE)	55-72-49-99	522	1.250
1-3 STRANDED XHHW (BLACK/BLACK-WHITE/BLACK-RED)	4 STRANDED (BARE)	55-80-64-99	488	1.101
1-4 STRANDED XHHW (BLACK/BLACK-BLUE/ BLACK-WHITE/BLACK-RED)	4 STRANDED (BARE)	55-99-63-99	609	1.206
For allowable ampacities, refer to NEC 310.15. Available with oversized grounding conductor when used for parallel feeds on special orders. Available in sizes up to 900 MCM.				

FEATURES

- UL Classified 1, 2, and 3 hour Through Penetration Firestop Systems: W-J-3037, W-L-3110, W-L-3113, W-L-3117, W-L-3120, W-L-3121, W-L-3160, C-AJ-3115, C-AJ-3140, C-AJ-3142, C-AJ-3145, C-AJ-3173, C-AJ-3202, C-AJ-4065, C-AJ-4066, F-C-3038.
- Cable reverse wound on reel for ease of pulling and installation. When pulling from coils, pull from inside to ensure ease of installation.
- Anti-short bushings are not required for use with MC cable per the NEC and UL

Phase Conductors are Black with Three Extruded Color Stripes

NUMBER OF CONDUCTORS	COLOR SEQUENCE 120/208Y
3	Black, Red Striped, and White Striped
4	Black, Red Striped, Blue Striped, and White Striped
Grounding Conductor	Bare

The Power of Connections.™



NEC TABLE 310.15(B)(16)- ALLOWABLE AMPACITY FOR 600V CONDUCTORS

SIZE AWG OR KCMIL	TEMPERATURE RATING OF CONDUCTOR		
	60°C (140°F)	75°C (167°F)	90°C (194°F)
	Types: TW, UF	Types: RHW, THHW, THW, THWN, XHHW, USE, ZW	Types: TBS, SA, SIS, RHH, RHW-2, THHN, THHW, THW- 2, THWN-2, USE-2, XHH, XHHW, XHHW-2, ZW-2
ALUMINUM or COPPER-CLAD ALUMINUM			
18	-	-	-
16	-	-	-
14	-	-	-
12	15	20	25
10	25	30	35
8	35	40	45
6	40	50	55
4	55	65	75
3	65	75	85
2	75	90	100
1	85	100	115
1/0	100	120	135
2/0	115	135	150
3/0	130	155	175
4/0	150	180	205
250	170	205	230
300	195	230	260
350	210	250	280
400	225	270	305
500	260	310	350
600	285	340	385
700	315	375	425
750	320	385	435
800	330	395	445
900	355	425	480
1000	375	445	500
1250	405	485	545
1500	435	520	585
1750	455	545	615
2000	470	560	630

Per NEC 310.15(B)(5), the ampacity of 4/C cables shall be reduced by a factor of 0.80 when the neutral is considered a current-carrying conductor.

Table is reprinted from NFPA 70-2014, the National Electric Code, © 2013 National Fire Protection Association, Quincy, Massachusetts 02269. This reprinted material is not the complete and official position of the National Fire Protection Association on the referenced subject, which is represented only by the standard in its entirety.