



## 1327A Multi-Conductor - DataBus® ISA/SP-50 FOUNDATION Fieldbus or PROFIBUS Cable



For more Information  
please call

1-800-Belden1



### General Description:

2 pair, 18 AWG stranded (7x26) tinned copper conductors, polyolefin insulation, individual & overall Beldfoil® shield (100% coverage), tinned copper drain wire, oil-resistant PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (mm)
2	18	7x26	TC - Tinned Copper	1.2192

Total Number of Conductors: 4

#### Insulation

Insulation Material:

Insulation Material
PO - Polyolefin

#### Inner Shield

Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Inner Shield Drain Wire AWG:

AWG
20

#### Outer Shield

Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
18	7x26	TC - Tinned Copper

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

#### Overall Cable

Overall Nominal Diameter: 11.176 mm

#### Pair

Pair Color Code Chart:

Number	Color
1	Blue & Orange Numbered 1
2	Blue & Orange Numbered 2

Pair Lay Length & Direction:

Lay Length (mm)	Twists (twist/m)
57.15	17.389

### Mechanical Characteristics (Overall)

Installation Temperature Range:	-25°C To +105°C
Operating Temperature Range:	-40°C To +105°C
Bulk Cable Weight:	119.651 Kg/Km
Max. Recommended Pulling Tension:	609.403 N
Min. Bend Radius/Minor Axis:	111.760 mm

## 1327A Multi-Conductor - DataBus® ISA/SP-50 FOUNDATION Fieldbus or PROFIBUS Cable

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMG, CMX-Outdoor, ITC, PLTC-ER
CEC/C(UL) Specification:	CMG
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	09/01/2006
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

#### Flame Test

UL Flame Test:	UL1685 FT4 Loading
IEC Flame Test:	60332-3-24 (Category C)
IEEE Flame Test:	1202

#### Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Sunlight Resistance:	Yes

#### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

### Electrical Characteristics (Overall)

#### Unaveraged Impedance:

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Impedance (Ohm)
	.03125			100

#### Nom. Inductance:

Inductance (µH/m)	0.62339
-------------------	---------

#### Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)	147.645
--------------------	---------

#### Nom. Mutual Capacitance:

Capacitance (pF/m)	78.744
--------------------	--------

#### Maximum Capacitance Unbalance:

Capacitance (pF/m)	3.9372
--------------------	--------

#### Nominal Velocity of Propagation:

VP (%)	66
--------	----

#### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)	19.2267
---------------------	---------

#### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)	16.0769
---------------------	---------

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C: 24.608 Ohm/km

#### Nom. Attenuation:

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Attenuation (dB/100m)
	.039			0.26248

#### Max. Attenuation:

()	Freq. (MHz)	Attenuation (dB/100m)
0.298571	0.039	0.299

## METRIC MEASUREMENT VERSION

### 1327A Multi-Conductor - DataBus® ISA/SP-50 FOUNDATION Fieldbus or PROFIBUS Cable

#### Max. Operating Voltage - UL:

Voltage
300 V RMS

#### Max. Recommended Current:

Description	Current
Per Conductor	5.2 Amps

**Other Electrical Characteristic 1:** Max Propagation Delay Change From 7.812 kHz to 39.06 kHz: 518 pS/ft

**Other Electrical Characteristic 2:** 31.25 KBits/sec

#### Notes (Overall)

**Notes:** Cables passes -40C cold bend per UL 1581.

#### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1327A 0031000	1,000 FT	98.000 LB	ORANGE	C	2 FS PR #18 PP FS FRPVC
1327A 0061000	1,000 FT	88.000 LB	BLUE, LIGHT	C	2 FS PR #18 PP FS FRPVC
1327A 0061640	1,640 FT	147.600 LB	BLUE, LIGHT	C	2 FS PR #18 PP FS FRPVC

#### Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1    Revision Date: 06-17-2016

© 2017 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).