



For more Information  
please call

1-800-Belden1



### General Description:

25 AWG stranded (19x37) .021" bare copper conductor, gas-injected foam HDPE insulation, Duofoil® + tinned copper braid shield (95% coverage), PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	25	19x37	BC - Bare Copper	0.5334

Total Number of Conductors: 1

#### Insulation

Insulation Material:

Insulation Material	Dia. (mm)
Gas-injected FHDPE - Foam High Density Polyethylene	2.3876

#### Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	95

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

#### Overall Cable

Overall Nominal Diameter: 3.810 mm

### Mechanical Characteristics (Overall)

Operating Temperature Range: -30°C To +75°C

UL Temperature Rating: 75°C

Bulk Cable Weight: 20.835 Kg/Km

Max. Recommended Pulling Tension: 120.101 N

Min. Bend Radius/Minor Axis: 38.100 mm

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

RG Type: Sub-miniature 59/U

**Flame Test**

UL Flame Test: UL1666 Vertical Shaft

**Suitability**

Suitability - Indoor: Yes

**Plenum/Non-Plenum**

Plenum (Y/N): No

**Electrical Characteristics (Overall)**

**Nom. Characteristic Impedance:**

Impedance (Ohm)

75

**Nom. Inductance:**

Inductance (µH/m)

0.305133

**Nom. Capacitance Conductor to Shield:**

Capacitance (pF/m)

54.1365

**Nominal Velocity of Propagation:**

VP (%)

82

**Nominal Delay:**

Delay (ns/m)

4.06844

**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/km)

89.8994

**Nominal Outer Shield DC Resistance:**

DCR @ 20°C (Ohm/km)

17.7174

**Nom. Attenuation:**

Freq. (MHz)	Attenuation (dB/100m)
1	1.54207
3.58	3.281
5	3.6091
7	4.2653
10	5.2496
67.5	11.8116
71.5	12.1397
88.5	13.4521
100	14.4364
135	16.405
143	16.7331
180	19.0298
270	23.2951
360	26.9042
540	33.1381
720	38.7158
750	39.372
1000	45.6059
1500	55.777
2000	64.3076
2250	68.2448
3000	78.744

**Max. Operating Voltage - UL:**

Voltage

300 V RMS

**Other Electrical Characteristic 1:**

Impedance tested in accordance with ASTM D-4566 paragraph 48.2, option 2 using a 75 Ohm fixed bridge and termination. 75 +/- 1.5 Ohms

**Other Electrical Characteristic 2:**

Return Loss tested in accordance with ASTM D-4566 paragraph 50.3, using a 75 Ohm fixed bridge and termination.

**Minimum Return Loss:**

Start Freq. (MHz)	Stop Freq. (MHz)	Min. RL (dB)
5.000	850.000	21.000

## METRIC MEASUREMENT VERSION

## 1865A Coax - Sub-Miniature

850.000	3000.000	18.000
---------	----------	--------

### Sweep Test

**Sweep Testing:** 100&#37; Sweep tested 5 MHz to 3 GHz.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1865A N3U1000	1,000 FT	16.000 LB	GREEN, MIL		#25 GIFHDPE SH FR PVC
1865A 0011000	1,000 FT	16.000 LB	BROWN	C	#25 GIFHDPE SH FR PVC
1865A 0021000	1,000 FT	16.000 LB	RED	C	#25 GIFHDPE SH FR PVC
1865A 0031000	1,000 FT	16.000 LB	ORANGE		#25 GIFHDPE SH FR PVC
1865A 0041000	1,000 FT	16.000 LB	YELLOW		#25 GIFHDPE SH FR PVC
1865A 0061000	1,000 FT	16.000 LB	BLUE, LIGHT	C	#25 GIFHDPE SH FR PVC
1865A 0071000	1,000 FT	16.000 LB	VIOLET	C	#25 GIFHDPE SH FR PVC
1865A 0081000	1,000 FT	16.000 LB	GRAY		#25 GIFHDPE SH FR PVC
1865A 0091000	1,000 FT	16.000 LB	WHITE	C	#25 GIFHDPE SH FR PVC
1865A 0101000	1,000 FT	16.000 LB	BLACK	C	#25 GIFHDPE SH FR PVC

#### Notes:

C = CRATE REEL PUT-UP.

Revision Number: 5    Revision Date: 04-30-2013

© 2017 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).