



**Part Number: 3106A**

RS-485, (1 pr) 22 AWG (7x30) TC & (1) 22 AWG (7x30) TC, FHDPE/PVC, Foil+TC Braid Shld, CM, PLTC

## Product Description

One 22 AWG pair stranded (7x30) tinned copper conductors & one 22 AWG stranded (7x30) tinned copper conductor, Datalene® (FHDPE) insulation, twisted pairs, overall Beldfoil® shield (100% coverage) plus a tinned copper braid (65% coverage), PVC jacket.

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Conductors	No. of Pairs
22	7x30	TC - Tinned Copper	0.03 in	1	1

Conductor Count: 3

#### Insulation

Material	Material Trade Name
FHDPE - Foamed High Density Polyethylene	Datalene®

#### Color Chart

Number	Color
1	White/Orange Stripe
2	Orange/White Stripe
3	Blue/White Stripe

#### Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	1	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	TC - Tinned Copper	22	7x30 mm
Braid	2	TC - Tinned Copper		65 %			

#### Outer Jacket Material

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.3 in

### Construction and Dimensions

#### Stranding

Lay Length
3 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
14.7 Ohm/1000ft	2.8 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield

11 pF/ft

20.9 pF/ft

**Inductance****Nominal Inductance**0.203  $\mu$ H/ft**Impedance****Nominal Characteristic Impedance** | **Nominal Characteristic Impedance Description**

120 Ohm

120

**High Frequency (Nominal/Typical)****Nom. Insertion Loss**

0.5 dB/100ft

**Delay****Nominal Velocity of Propagation (VP) [%]**

78 %

**Current****Max. Recommended Current [A]**

2.7 Amps per conductor @ 25°C

**Voltage****UL Voltage Rating**

300 V RMS (NEC Type PLTC)

300 V RMS (NEC Type CM)

**Temperature Range**

Non-UL Temp Rating:	60°C
UL Temp Rating:	60°C
Operating Temp Range:	-20°C To +60°C

**Mechanical Characteristics**

Bulk Cable Weight:	48 lbs/1000ft
Max Recommended Pulling Tension:	65 lbs
Min Bend Radius/Minor Axis:	3 in

**Standards**

NEC/(UL) Specification:	CM, PLTC
CEC/C(UL) Specification:	CM
CPR Euroclass:	Eca

**Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-10-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

**Suitability**

Suitability - Oil Resistance:	Yes
-------------------------------	-----

Suitability - Sunlight Resistance:	Yes
------------------------------------	-----

### Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1685 UL Loading
CSA Flammability:	FT1

### Part Number

Plenum (Y/N):	No
---------------	----

### Variants

Item #	Color
3106A.00152	BLACK
3106A.001525	BLACK
3106A.00305	BLACK
3106A 0101000	BLACK
3106A 010500	BLACK
3106A 0105000	BLACK

### Product Notes

Notes:	Oil Resistance: Passes Oil Res II Per UL1277, Table 10.17. For CPE jacketed version order YR46721.
Footnote:	CRATE REEL PUT-UP.
Footnote:	FINAL PUT-UP LENGTH MAY VARY -0% TO +10% FROM LENGTH SHOWN.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.