

579945 Composite - CCTV Plus Audio or Powr or Pan and Tilt CCTV Control Applications



For more Information
please call

1-800-Belden1



General Description:

PTZ (CCTV+Power/Audio) Cable, Rated-CMG, 1-RG59 25 AWG solid bare copper with foam polyolefin, 95% bare copper braid, 1-20 AWG stranded bare copper pair with PVC insulation, Siamese with PVC jacket

Coax

Physical Characteristics

Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	25	Solid	BC - Bare Copper	0.457

Insulation

Insulation Material:

Insulation Material	Dia. (mm)
Gas-injected FPE - Foam Polyethylene	2.159

Inner Shield

Inner Shield Material:

Type	Inner Shield Material	% Coverage (%)
Braid	BC - Bare Copper	95

Electrical Characteristics

Nom. Characteristic Impedance:

Impedance (Ohm)
75

Nom. Inductance:

Inductance (µH/m)
0.358

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)
55.449

Nominal Velocity of Propagation:

VP (%)
80.000

Nominal Delay:

Delay (ns/m)
4.167

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
101.711

Nom. Inner Shield DC Resistance:

DCR @ 20°C (Ohm/km)
18.374

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
1.000	1.476
5.000	2.953
10.000	4.265
50.000	9.843
100.000	13.452
200.000	19.686
400.000	28.217
700.000	38.060
900.000	44.294
1000.000	47.575

579945 Composite - CCTV Plus Audio or Powr or Pan and Tilt CCTV Control Applications

Twisted Pair

Physical Characteristics

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (mm)
1	20	7x28	BC - Bare Copper	0.960

Insulation

Insulation Material:

Insulation Material	Dia. (mm)
PVC - Polyvinyl Chloride	1.422

Twisted Pair Color Code Chart:

Number	Color
1	Black and Red

Inner Shield

Inner Shield Material:

Inner Shield Material
Unshielded

Electrical Characteristics

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
85.306

Physical Characteristics (Overall)

Conductor

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cable

Overall Nominal Diameter: 3.835,8.433 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +75°C

Bulk Cable Weight: 40.181 Kg/Km

Max. Recommended Pulling Tension: 177.928 N

Min. Bend Radius/Minor Axis: 63.500 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CM

CEC/C(UL) Specification: CM

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Flame Test

UL Flame Test: UL1685 UL Loading

Suitability

Suitability - Indoor: Yes

Plenum/Non-Plenum

Plenum (Y/N): No

Plenum Number: 679948

579945 Composite - CCTV Plus Audio or Powr or Pan and Tilt CCTV Control Applications

Electrical Characteristics (Overall)

Max. Operating Voltage - UL:

Voltage
300 V RMS

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
579945 0091000	1,000 FT	29.000 LB	WHITE		RG59 MINI#25 + 2C18 CMG SIAM
579945 009500	500 FT	15.000 LB	WHITE		RG59 MINI#25 + 2C18 CMG SIAM
579945 0101000	1,000 FT	29.000 LB	BLACK	C	RG59 MINI#25 + 2C18 CMG SIAM

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 0 Revision Date: 03-13-2013

© 2016 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.