

6220UL Multi-Conductor - Commercial Applications - 2 Conductors Cabled



For more Information
please call

1-800-Belden1



General Description:

Fire Alarm Cable, Plenum-FPLP, 2-16 AWG solid bare copper conductors with Flamarrest® insulation, Flamarrest® jacket with ripcord

Usage (Overall)

Suitable Applications: Fire Protection, Alarm, Signal, Monitor/Detection, Audio Circuits, Control Circuits, Initiating Circuits, Notification Circuits

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
2	16	Solid	BC - Bare Copper

Total Number of Conductors: 2

Insulation

Insulation Material:

Insulation Trade Name	Insulation Material	Wall Thickness (mm)
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride	0.203

Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material	Nom. Wall Thickness (mm)
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride	0.381

Outer Jacket Ripcord: Yes

Overall Cable

Overall Cabling Lay Length & Direction:

Length (mm)	Twists (twist/m)
69.849725	14.4364

Overall Cabling Color Code Chart:

Number	Color
1	Black
2	Red

Overall Nominal Diameter: 4.216 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: 0°C To +75°C

UL Temperature Rating: 75°C

Bulk Cable Weight: 34.973 Kg/Km

Max. Recommended Pulling Tension: 277.568 N

Min. Bend Radius/Minor Axis: 41.275 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: FPLP

NEC Articles: 760

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

METRIC MEASUREMENT VERSION

6220UL Multi-Conductor - Commercial Applications - 2 Conductors Cabled

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes
Other Specification:	California State Fire Marshall

Flame Test

UL Flame Test:	NFPA 262
----------------	----------

Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	5220UL

Electrical Characteristics (Overall)

Nom. Inductance:

Inductance (µH/m)
0.49215

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
121.397

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
12.6319

Max. Operating Voltage - UL:

Voltage
300 V RMS

Max. Recommended Current:

Current
6.3 Amps per conductor @ 25°C

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
6220UL D15U1000	1,000 FT	24.000 LB	BLUE		2 #16 FLRST FLRST
6220UL D151000	1,000 FT	24.000 LB	BLUE		2 #16 FLRST FLRST
6220UL 001U1000	1,000 FT	24.000 LB	BROWN		2 #16 FLRST FLRST
6220UL 002A1000	1,000 FT	26.000 LB	RED		2 #16 FLRST FLRST
6220UL 002U1000	1,000 FT	24.000 LB	RED		2 #16 FLRST FLRST
6220UL 0021000	1,000 FT	24.000 LB	RED	C	2 #16 FLRST FLRST
6220UL 002500	500 FT	12.000 LB	RED		2 #16 FLRST FLRST
6220UL 003C500	500 FT	11.000 LB	ORANGE		2 #16 FLRST FLRST
6220UL 003U1000	1,000 FT	24.000 LB	ORANGE		2 #16 FLRST FLRST
6220UL 004C500	500 FT	11.000 LB	YELLOW		2 #16 FLRST FLRST
6220UL 004U1000	1,000 FT	24.000 LB	YELLOW		2 #16 FLRST FLRST
6220UL 0041000	1,000 FT	24.000 LB	YELLOW		2 #16 FLRST FLRST
6220UL 007U1000	1,000 FT	24.000 LB	VIOLET		2 #16 FLRST FLRST
6220UL 0091000	1,000 FT	24.000 LB	WHITE		2 #16 FLRST FLRST
6220UL 0101000	1,000 FT	24.000 LB	BLACK		2 #16 FLRST FLRST

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 03-13-2013

© 2017 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the

METRIC MEASUREMENT VERSION

6220UL Multi-Conductor - Commercial Applications - 2 Conductors Cabled

product.
Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).