

## 7951A Composite - Composite Data, Audio, Video, Security and Control Cable



For more Information  
please call

1-800-Belden1



### General Description:

Composite - (1)Cat 5 4-pair, 24 AWG unshielded plus (4) 18 AWG stranded (19x30) bare copper conductors, polyolefin Insulation on the pairs; PVC insulation on the conductors, overall F-R PVC jacket. Jacket sequentially marked.

### Usage (Overall)

Suitable Applications:

Keypads, Control Panels, Touch Panel Controls, Home Theater, A/V Equipment, Projectors, Screens, Window Treatments, Lighting, Security, Security Cameras, Home Automation, Energy Control

### Twisted Pair

#### Physical Characteristics

##### Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
4	24	Solid	BC - Bare Copper	0.020

##### Insulation

Insulation Material:

Insulation Material	Dia. (in.)
PO - Polyolefin	0.036

Twisted Pair Color Code Chart:

Number	Color
1	White/Blue Stripe and Blue
2	White/Orange Stripe and Orange
3	White/Green Stripe and Green
4	White/Brown Stripe and Brown

##### Individual Shield

##### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (in.)
0.195

Outer Jacket Ripcord:

Yes

Outer Jacket Color Code Chart:

Color
Lt Green

### Electrical Characteristics

Premise Cable Electricals:

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. SRL (dB)	Fitted Imp. (Ohms)
1.0	2.000	62	N/A	23	100 ± 15%
4.0	4.100	53	N/A	23	100 ± 15%
8.0	5.800	48	N/A	23	100 ± 15%
10.0	6.500	47	N/A	23	100 ± 15%
16.0	8.200	44	N/A	23	100 ± 15%
20.0	9.300	42	N/A	23	100 ± 15%
25.0	10.400	41	N/A	22	100 ± 15%
31.25	11.700	39	N/A	21	100 ± 15%
62.5	17.000	35	N/A	18	100 ± 15%
100	22.000	32	N/A	16	100 ± 15%

## 7951A Composite - Composite Data, Audio, Video, Security and Control Cable

### Multi Conductor

#### Physical Characteristics

##### Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (in.)
4	18	19x30	BC - Bare Copper	0.044

##### Insulation

Insulation Material:

Insulation Material	Dia. (in.)
PVC - Polyvinyl Chloride	0.066

Insulation Color Code Chart:

Number	Color
1	Red
2	White
3	Green
4	Black

##### Individual Shield

#### Electrical Characteristics

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
15.000

Nominal Velocity of Propagation:

VP (%)
70.000

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
9.380

Max. Operating Voltage - UL:

Voltage
300 V RMS

Max. Recommended Current:

Current
4 Amps per conductor @ 25°C

Other Electrical Characteristic 1:

Third party verified to TIA/EIA 568-B.2, Category 5

### Physical Characteristics (Overall)

#### Conductor

##### Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

##### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Ripcord:

Yes

#### Overall Cable

Overall Nominal Diameter:

0.407 in.

### Mechanical Characteristics (Overall)

Operating Temperature Range:

-20°C To +75°C

Bulk Cable Weight:

74 lbs/1000 ft.

Max. Recommended Pulling Tension:

123 lbs.

Min. Bend Radius/Minor Axis:

4.500 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification:

CMR

CEC/C(UL) Specification:

CMG

EU Directive 2011/65/EU (ROHS II):

Yes

## 7951A Composite - Composite Data, Audio, Video, Security and Control Cable

EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Other Specification:	NEMA WC-63/1. Category 5

### Flame Test

UL Flame Test:	UL1666 Riser
CSA Flame Test:	FT4

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

### Electrical Characteristics (Overall)

Max. Operating Voltage - UL:

<b>Voltage</b>
300 V RMS

### Notes (Overall)

**Notes:** Overall jacket sequentially marked.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0    Revision Date: 09-10-2013

© 2016 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).