



For more Information
please call

1-800-Belden1



General Description:

20 AWG solid .031" bare copper conductor, polyethylene insulation, tinned copper/bare copper double braid shield (95% coverage), polyethylene jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	20	Solid	BC - Bare Copper	0.7874

Total Number of Conductors: 1

Insulation

Insulation Material:

Insulation Material	Dia. (mm)
PE - Polyethylene	5.0292

Outer Shield

Outer Shield Material:

Layer #	Type	Outer Shield Material	Coverage (%)
1	Braid	TC - Tinned Copper	95.000
2	Braid	TC - Tinned Copper	95.000

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PE - Polyethylene

Overall Cable

Overall Nominal Diameter: 7.747 mm

Mechanical Characteristics (Overall)

Operating Temperature Range:	-55°C To +80°C
Non-UL Temperature Rating:	80°C
Bulk Cable Weight:	102.686 Kg/Km
Max. Recommended Pulling Tension:	747.298 N
Min. Bend Radius/Minor Axis:	76.200 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	No
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes
RG Type:	59/U

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	88281

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)
75

Nom. Inductance:

Inductance (µH/m)
0.429811

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)
68.901

Nominal Velocity of Propagation:

VP (%)
66

Nominal Delay:

Delay (ns/m)
5.05274

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
32.4819

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
3.6091

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
1	0.9843
3.6	1.6405
10.0	2.6248
71.5	6.8901
135	9.843
270	14.1083
360	16.7331
540	20.6703
720	24.2794
750	24.9356
1000	30.1852

Max. Operating Voltage - Non-UL:

Voltage
2900 V RMS

Other Electrical Characteristic 1:

Impedance tested in accordance with ASTM D-4566 paragraph 43.2, option 2 using a 75 Ohm fixed bridge and termination. 75 +/- 1.5 Ohms

Other Electrical Characteristic 2:

Return Loss tested in accordance with ASTM D-4566 paragraph 45.3, using a 75 Ohm fixed bridge and termination.

Minimum Structural Return Loss:

Start Freq. (MHz)	Stop Freq. (MHz)	Min. SRL (dB)
5	216	27
217	850	23

Sweep Test

Sweep Testing: 100% Sweep tested 5MHz to 850MHz.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
600006215	1 EA	0.416 LB			RSTS 5-183/3 M
8281 0021000	1,000 FT	73.000 LB	RED	C	75 OHM VIDEO COAX
8281 002500	500 FT	37.500 LB	RED	C	75 OHM VIDEO COAX
8281 0031000	1,000 FT	73.000 LB	ORANGE	C	75 OHM VIDEO COAX
8281 0041000	1,000 FT	73.000 LB	YELLOW	C	75 OHM VIDEO COAX
8281 004500	500 FT	37.500 LB	YELLOW		75 OHM VIDEO COAX
8281 0051000	1,000 FT	73.000 LB	GREEN, DARK	C	75 OHM VIDEO COAX
8281 005500	500 FT	37.500 LB	GREEN, DARK	C	75 OHM VIDEO COAX
8281 0061000	1,000 FT	73.000 LB	BLUE, LIGHT	C	75 OHM VIDEO COAX
8281 006500	500 FT	37.500 LB	BLUE, LIGHT		75 OHM VIDEO COAX
8281 0091000	1,000 FT	73.000 LB	WHITE	C	75 OHM VIDEO COAX

METRIC MEASUREMENT VERSION

8281 Coax - Double Braided RG-59/U Type

8281 0101000	1,000 FT	73.000 LB	BLACK	C	75 OHM VIDEO COAX
8281 010500	500 FT	37.500 LB	BLACK	C	75 OHM VIDEO COAX
8281 0105000	5,000 FT	380.000 LB	BLACK	C Z	75 OHM VIDEO COAX

Notes:

C = CRATE REEL PUT-UP.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND(+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 2 Revision Date: 07-29-2013

© 2017 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.