



For more Information
please call

1-800-Belden1



General Description:

20 AWG stranded (7x28) TC conductors, plenum, FEP Teflon® insulation, twisted pairs, overall polyester isolation tape + Duofoil + TC braid shield (95% coverage), drain wire, light gray fluorocopolymer (PVDF) jacket.

Usage (Overall)

Suitable Applications: 10Base5 Transceiver

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
4	20	7x28	TC - Tinned Copper

Total Number of Conductors: 8

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
FFEP/Solid FEP - Foam Fluorinated Ethylene Propylene/Solid Fluorinated Ethylene Propylene	0.279

Inner Shield

Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil® (Z-Fold®)	Tape	Aluminum Foil-Polyester Tape	100

Inner Shield Drain Wire AWG:

AWG
22

Inner Shield Drain Wire Stranding: 7x30

Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	95

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
PVDF - Fluorocopolymer	0.406

Overall Cable

Overall Cabling Separator Material: Polyester Tape

Overall Nominal Diameter: 9.398 mm

Pair

Pair Color Code Chart:

Number	Color
1	Gray & White
2	Yellow & Orange
3	Blue & Green
4	Red & Black

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +150°C

UL Temperature Rating: 150°C

Bulk Cable Weight: 138.403 Kg/Km

Max. Recommended Pulling Tension:	894.088 N
Min. Bend Radius/Minor Axis:	95.250 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP
IEEE Specification:	IEEE802.3
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Customer Part Number Reference Specification:	DEC Part No. 17-01319-00

Flame Test

UL Flame Test:	NFPA 262
CSA Flame Test:	FT6

Suitability

Suitability - Outdoor:	Yes
Suitability - Burial:	Yes

Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	9901

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)	Tolerance (Ohms)
78	± 5

Nom. Inductance:

Inductance (µH/m)
0.6562

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
54.7927

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/m)
96.7895

Nominal Velocity of Propagation:

VP (%)
78

Nominal Delay:

Delay (ns/m)
4.2653

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
34.4505

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
4.9215

Max. Attenuation:

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Attenuation (dB/100 m)
	10			6

Max. Operating Voltage - UL:

METRIC MEASUREMENT VERSION

89901 Multi-Conductor - 10 Base 5 Transceiver

Voltage

300 V RMS

Max. Recommended Current:**Current**

2.8 Amps per conductor @ 25°C

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
89901 E4X1000	1,000 FT	102.000 LB	GRAY, LIGHT DEC	C	4#20 SHPR SLF W/.051"VGM
89901 E4X500	500 FT	50.500 LB	GRAY, LIGHT DEC	C	4#20 SHPR SLF W/.051"VGM

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 11-07-2012

© 2017 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).