

For more Information
please call

1-800-Belden1



General Description:

93 ohm, RG-62A/U type, 22 AWG solid .025" bare copper-covered steel conductor, semi-solid polyethylene insulation, bare copper braid shield (95% coverage), high-density polyethylene jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	22	Solid	BCCS - Bare Copper Covered Steel	0.635

Total Number of Conductors: 1

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)	Dia. (mm)
Semi-Solid PE - Semi-Solid Polyethylene	0.660	3.708

Tracer

Tracer AWG: Solid

Outer Shield

Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	BC - Bare Copper	95

Outer Shield Flooding Grease: Polyethylene

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
HDPE - High Density Polyethylene	0.838

Overall Cable

Overall Nominal Diameter: 6.147 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: -55°C To +80°C

Non-UL Temperature Rating: 80°C

Bulk Cable Weight: 44.646 Kg/Km

Max. Recommended Pulling Tension: 373.649 N

Min. Bend Radius/Minor Axis: 63.500 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MIL Order #39 (China RoHS): Yes

RG Type: 62A/U

Suitability

Suitability - Outdoor: Yes

Suitability - Burial: Yes

Plenum/Non-Plenum

Plenum (Y/N): No

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)
93

Nom. Inductance:

Inductance (µH/m)
0.380596

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)
44.2935

Nominal Velocity of Propagation:

VP (%)
84

Nominal Delay:

Delay (ns/m)
3.9372

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
135.177

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
9.5149

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
1	0.9843
10	2.9529
50	6.2339
100	8.8587
200	12.4678
400	17.3893
700	23.9513
900	26.9042
1000	28.5447

Max. Operating Voltage - Non-UL:

Voltage
300 V RMS

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9228 0101000	1,000 FT	33.000 LB	BLACK	C	RG-62A/U TYPE COAX
9228 0102000	2,000 FT	68.000 LB	BLACK	C	RG-62A/U TYPE COAX
9228 0105000	500 FT	16.500 LB	BLACK	C	RG-62A/U TYPE COAX
9228 0105000	5,000 FT	170.000 LB	BLACK	C	RG-62A/U TYPE COAX

Notes:
C = CRATE REEL PUT-UP.

Revision Number: 4 Revision Date: 09-09-2015

© 2017 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the

Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

9228 Coax - 93 Ohm

product.
Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).