

For more Information
please call

1-800-Belden1



General Description:

22 AWG stranded (7x30) TC conductors, polyolefin insulation, dual twisted pairs, overall Beldfoil® shield (100% coverage), 22 AWG stranded TC drain wire, PVC jacket in zip-cord construction.

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
2	22	7x30	TC - Tinned Copper

Total Number of Conductors: 4

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
PO - Polyolefin	0.2032

Outer Shield

Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
22	7x30	TC - Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.508

Overall Cable

Overall Nominal Diameter: 3.429 x 6.858 mm

Pair

Pair Color Code Chart:

Number	Color
1	Black & Red
2	Black & Red

Mechanical Characteristics (Overall)

Operating Temperature Range: -30°C To +105°C

UL Temperature Rating: 105°C

Bulk Cable Weight: 40.181 Kg/Km

Max. Recommended Pulling Tension: 240.203 N

Min. Bend Radius/Minor Axis: 38.100 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/(UL) Specification: CMR

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

METRIC MEASUREMENT VERSION

9451D Multi-Conductor - Double-Pair Cable

EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	UL1666 Vertical Shaft
CSA Flame Test:	FT4

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)

45

Nom. Inductance:

Inductance (µH/m)

0.52496

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)

111.554

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/m)

219.827

Nominal Velocity of Propagation:

VP (%)

66

Nominal Delay:

Delay (ns/m)

4.9215

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

46.2621

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)

46.9183

Max. Operating Voltage - UL:

Voltage

300 V RMS

Max. Recommended Current:

Current

2.9 Amps per conductor @ 25°C

Notes (Overall)

Notes: The jacket and shield are bonded so both can be removed on automatic stripping equipment. Drain wire is inside foil shield. For cross-connect use with 1814R (et. al.) Snake Cables.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9451D A5QU1000	1,000 FT	29.000 LB	RED & GREEN		2 BONDED #22 FSPR PO FRPVC
9451D A5Q2000	2,000 FT	58.000 LB	RED & GREEN		2 BONDED #22 FSPR PO FRPVC
9451D G04U1000	1,000 FT	29.000 LB	RED & PURPLE		2 BONDED #22 FSPR PO FRPVC
9451D J77U1000	1,000 FT	29.000 LB	USE 061		2 BONDED #22 FSPR PO FRPVC
9451D 053U1000	1,000 FT	29.000 LB	RED & GRAY		2 BONDED #22 FSPR PO FRPVC

Revision Number: 1 Revision Date: 08-22-2012

© 2017 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.

METRIC MEASUREMENT VERSION

9451D Multi-Conductor - Double-Pair Cable

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).