

9581 Multi-Conductor - Power-Limited Fire Protective Signal Circ Cabl, 2 Cdrs Cabld



For more Information
please call

1-800-Belden1



General Description:

14 AWG solid bare copper conductors, conductors cabled, PVC insulation, Beldfoil® shield (100% coverage), 16 AWG stranded TC drain wire, PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
2	14	Solid	BC - Bare Copper

Total Number of Conductors: 2

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.5588

Outer Shield

Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
16	Stranded	TC - Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	1.0668

Overall Cable

Overall Cabling Lay Length & Direction:

Length (mm)	Direction	Twists (twist/m)
50.800	Left Hand	19.686

Overall Cabling Color Code Chart:

Number	Color
1	Black
2	Red

Overall Nominal Diameter: 7.772 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +105°C

UL Temperature Rating: 105°C

Bulk Cable Weight: 86.316 Kg/Km

Max. Recommended Pulling Tension: 551.577 N

Min. Bend Radius/Minor Axis: 82.550 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	FPLR
NEC Articles:	760
CEC/C(UL) Specification:	FAS105
AWM Specification:	UL Style 2464 (300 V 80°C)
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes

METRIC MEASUREMENT VERSION

9581 Multi-Conductor - Power-Limited Fire Protective Signal Circ Cabl, 2 Cdrs Cabld

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes
Other Specification:	California State Fire Marshall

Flame Test

UL Flame Test:	UL1666 Riser
CSA Flame Test:	FT4

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)

Nom. Inductance:

Inductance (µH/m)

0.59058

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)

180.455

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/m)

344.505

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

8.2025

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)

12.4678

Max. Operating Voltage - UL:

Voltage

300 V RMS

Max. Recommended Current:

Current

18 Amps per conductor @ 25°C ambient

Notes (Overall)

Notes: This cable passes the UL 1685 70,000 BTU Flame Test (comparable to the IEEE 383 Flame Test) and is listed by the California State Fire Marshall. Component Recognized UL 2464, 300 V 80°C.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9581 002U500	500 FT	31.500 LB	RED		2 #14 PVC SHLD PVC
9581 0021000	1,000 FT	63.000 LB	RED	C	2 #14 PVC SHLD PVC

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 4 Revision Date: 08-02-2013

© 2017 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification.

METRIC MEASUREMENT VERSION

9581 Multi-Conductor - Power-Limited Fire Protective Signal Circ Cabl, 2 Cdrs Cabl

Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.
Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).