


PRODUCT SPECIFICATION



PRODUCT NUMBER: 2232A4T
DESCRIPTION: 22 1007/1569

DIAMETER: 0.061
TOLERANCE +/-: 0.003

GAUGE: 22 AWG
CONDUCTORS: 1
STRANDING: 7/0096 TC LHL
INSULATION: PVC
VOLTAGE: 300V DC
TEMPERATURE: 80/105 C
STYLE: 1569/1007/TR-64
PRINT LEGEND: E511593 22 AWG (0.324mm²) UR AWM
1569 105C or 1007 80C 300V VW-1 --
301259 CSA TR-64 90C FT1 or AWM I A/B
105C 300V FT1
NOTES: MIN TEMP: -10C PER UL758



NOM WALL: 0.015
MINIMUM WALL: 0.013

Tolerances unless otherwise noted: FRACTIONS +/- 1/32, DECIMALS +/- 0.03 (2PL) +/-0.005 (3PL)

Confidential: This drawing and its information are the exclusive and confidential property of Sequel Wire and Cable, LLC and are not to be disclosed, duplicated, distributed, or otherwise used without the written consent of Sequel Wire and Cable, LLC. All rights reserved.

Date	Revision	ECN	Description
04/01/2024	3		updated copper description for operation clarification