

157-01300

Article Number: 157-01300



Description: Stud Mount Tie for .25", 120lb Tensile, 16.0" Long, PA66HIRHSUV, Black, 50/pkg

Base Data	Local Order Number	T120RSM0HIRK2
	Type	T120RSM
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> • Mounts and secures bundles all in one component; providing quick installation time. • Mounts quickly and securely for easy installation.
	Quantity Per	bag
	Product Description	HellermannTyton stud mount tie designed for use on a 1/4" threaded stud or exposed threads of a machine screw.
	Short Description	Stud Mount Tie for .25", 120lb Tensile, 16.0" Long, PA66HIRHSUV, Black, 50/pkg
Product Dimensions	Minimum Tensile Strength (Imperial)	120.0lbs
	Minimum Tensile Strength (Metric)	535N
	Length L (Imperial)	16.0"
	Length L (Metric)	405.0mm
	Fixation Method	Weld Stud Fixing
	Identification Plate Position	none
	Releasable Closure	No
	Tie Closure	plastic pawl
	Variant	Inside Serrated
	Width W (Imperial)	0.3"
	Width W (Metric)	7.6mm
	Height H (Imperial)	.77"
	Height H (Metric)	19.50mm
	Bundle Diameter Min. (Imperial)	0.2"
	Bundle Diameter Min. (Metric)	5.0mm
Bundle Diameter Max. (Imperial)	4.0"	

157-01300



Product Dimensions	Bundle Diameter Max. (Metric)	101.0mm
	Stud Diameter (Imperial)	0.25"
	Stud Diameter (Metric)	6.3 mm
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
	Material Shortcut	PA66HIRHSUV
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	bag