

"Stay Connected" with



Solar Power Components

a PennEngineering® Company



Heyco® Nylon Snap-In Bushings for American Electrical Knock Out Holes

Heyco® K. O. Snap Bushings

TRADE SIZE	MOUNTING HOLE DIAMETER		PART NO. Black	DESCRIPTION	INSIDE DIAMETER	
	in.	mm.			in.	mm.
Multiple Locking Steps for Box Thickness up to .125" (3,2 mm)						
1/2	.875	22,2	2126	SB 875-11	.69	17,5
3/4	1.093-1.125	27,8-28,6	2166	SB 1093-15	.94	23,8
1	1.375	34,9	2210	SB 1375-16	1.01	25,8
1-1/4	1.750	44,5	2300	SB 1750-22	1.38	34,9
1-1/2	2.000	50,8	2406	SB 2000-28	1.75	44,5
Multiple Locking Steps for Box Thickness up to .250" (6,4 mm)						
1/2	.875	22,2	3104	SBT 875-11	.69	17,5
3/4	1.093-1.125	27,8-28,6	3128	SBT 1093-15	.94	23,8
1	1.375	34,9	3110	SBT 1375-16	1.00	25,4
1-1/4	1.750	44,5	3114	SBT 1750-22	1.38	34,9
1-1/2	2.000	50,8	3116	SBT 2000-26	1.63	41,3
2	2.500	63,5	2420	SB 2.500-31	1.97	50,0

Standard color black. Consult Heyco for other colors.

Heyco® K. O. Universal Bushings

TRADE SIZE	MOUNTING HOLE DIAMETER		PART NO. Black	DESCRIPTION	INSIDE DIAMETER	
	in.	mm.			in.	mm.
Multiple Locking Steps for Panel Thickness up to .125" (3,2 mm)						
1/2	.875	22,2	2119	UB 875	.56	14,3
3/4	1.093-1.125	27,8-28,6	2157	UB 1093	.81	20,6
1	1.375	34,9	2184	UB 1375	1.00	25,4
1-1/4	1.750	44,5	2298	UB 1750	1.38	34,9
1-1/2	2.000	50,8	2422	UB 2000	1.64	41,6
Multiple Locking Steps for Panel Thickness up to .250" (6,4 mm)						
1/2	.875	22,2	3120	UBT 875	.56	14,3
3/4	1.093-1.125	27,8-28,6	3002	UBT 1093	.81	20,6
1	1.375	34,9	3003	UBT 1375	1.00	25,4
2	2.500	63,5	2440	UB 2.500	1.97	50,0


Standard color black. Consult Heyco for other colors.

Heyco® K. O. Reducer Bushings


Multiple Locking Steps for Panel Thickness up to .125" (3,2 mm)

TRADE SIZE	MOUNTING HOLE DIAMETER		PART NO. Black	DESCRIPTION	INSIDE DIAMETER	
	in.	mm.			in.	mm.
1/2	.875	22,2	2110	SB 875-6	.38	9,5
			2113	SB 875-7	.44	11,1
			2116	SB 875-8	.50	12,7
			2120	SB 875-9	.56	14,3
			2123	SB 875-10	.63	15,9
3/4	1.093 - 1.125	27,8-28,6	2160	SB 1093-13	.81	20,6
			2163	SB 1093-14	.88	22,2
1	1.375	34,9	2207	SB 1375-14	.88	22,2
1-1/2	2.000	50,8	2400	SB 2000-26	1.64	41,6

Standard color black. Consult Heyco for other colors.



K.O. Snap and Reducer Bushings



K.O. Universal Bushings

Quick Specs

Material
Certifications



Nylon 6/6
Recognized under the Component Program of Underwriters' Laboratories, File E15331



Certified by Canadian Standards Association, File 8919

Flammability Rating
Temperature Range

94V-2
-04°F (-18°C) to 221°F (105°C)