



Heyco® Nylon Snap-In Bushings for American Electrical Knock Out Holes

Heyco® K. O. Open/Closed Universal Bushings

TRADE SIZE	MOUNTING HOLE DIAMETER		PART NO. Black	DESCRIPTION	INSIDE DIAMETER	
	in.	mm.			in.	mm.
Multiple Locking Steps for Panel Thickness up to .125" (3,2 mm)						
1/2	.875	22,2	2119SP	OCUB 875	.56	14,3
3/4	1.093-1.125	27,8-28,6	2157SP	OCUB 1093	.81	20,6
1	1.375	34,9	2184SP	OCUB 1375	1.00	25,4
1-1/2	2.000	50,8	2422SP	OCUB 2.000	1.64	41,7
Multiple Locking Steps for Panel Thickness up to .250" (6,4 mm)						
2	2.500	63,5	2440SP	OCUB 2.5	1.97	43,2



Standard color black. Consult Heyco for other colors.

Heyco® K. O. Smooth Bore Bushings*

TRADE SIZE	MOUNTING HOLE DIAMETER		PART NO. Black	DESCRIPTION	INSIDE DIAMETER	
	in.	mm.			in.	mm.
Single Locking Step for Panel Thickness up to .062" (1,6 mm)						
1/2	.875	22,3	2540	S 87	.52	13,2
Multiple Locking Steps for Panel Thickness up to .125" (3,2 mm)						
1/2	.875	22,3	2552	S 875-9	.56	14,2
3/4	1.093-1.125	27,8-28,6	2555	S 1093-10	.63	16,0


Standard color black. Consult Heyco for other colors.

*For NPT Threaded Smooth Bore Bushings, see page 2-22.




K.O. Open/Closed Universal Bushings

K.O. Open/Closed Bushings



K.O. Smooth Bore Bushings



Armor Bushings

Heyco® K. O. Open/Closed Bushings

TRADE SIZE	MOUNTING HOLE DIAMETER		PART NO. Black	DESCRIPTION	INSIDE DIAMETER	
	in.	mm.			in.	mm.
Multiple Locking Steps for Panel Thickness up to .125" (3,2 mm)						
1/2	.875	22,2	2874	OCB 875	.67	17,0
3/4	1.093-1.125	27,8-28,6	2879	OCB 1093	.88	20,6
1	1.375	34,9	2882	OCB 1375	1.17	29,8
1-1/2	2.000	50,8	2900	OCB 2.000	1.73	43,9
Multiple Locking Steps for Panel Thickness up to .250" (6,4 mm)						
2	2.500	63,5	2909	OCB 2.5	2.00	50,8

Standard color black. Consult Heyco for other colors.

Heyco® Polyethylene* Armor Bushings

WILL FIT THESE ARMORED CABLES AWG/Conductors	PART NO.	DESC.	PART DIMENSIONS			
			Inside Diameter		Head Diameter	
			in.	mm.	in.	mm.
14/2, 14/3, 12/2, 12/3	2264	AB 0	.37	9,4	.68	17,3
14/4, 6/1, 4/1	2265	AB 1	.44	11,2	.70	17,8
12/4, 10/2, 10/3, 2/1	2266	AB 2	.57	14,0	.85	21,6
10/4, 8/2, 8/3, 1/1	2267	AB 3	.73	18,5	1.02	25,9

Standard color red.

*High dielectric polyethylene.

Material	OCUB & OCB Nylon 6/6
Certifications	Recognized under the Component Program of Underwriters' Laboratories, File E15331 Certified by Canadian Standards Association, File 8919
Flammability Rating	94V-2
Temperature Range	-04°F (-18°C) to 221°F (105°C)

Armor Bushings
High Dielectric Polyethylene
Listed under Underwriters' Laboratories, File E51579
Certified by Canadian Standards Association, File 213253

94-HB
-04°F (-18°C) to 221°F (105°C)