

“Stay Connected” with



Solar Power Components

a PennEngineering® Company



Heyco® Snap-in Nylon Vent and Louvered Plugs for American Electrical Knock Out Holes



Heyco® K. O. Vent Plugs

TRADE SIZE	MOUNTING HOLE DIAMETER		PART NO. Black	DESCRIPTION	PART DIMENSIONS		
	in.	mm.			No. of Vent Holes	Head Diameter	
					in.	mm.	
Multiple Locking Steps for Box Thickness up to .125" (3,2 mm)							
1/2	.875	22,2	2697	VP 875	9	1.02	25,8
3/4	1.093-1.125	27,8-28,6	2726	VP 1093	9	1.22	30,9
1	1.375	34,9	2756	VP 1375	11	1.50	38,1
1-1/4	1.750	44,5	2776	VP 1750	13	1.91	48,4
1-1/2	2.000	50,8	2786	VP 2000	19	2.14	54,4
Multiple Locking Steps for Box Thickness up to .250" (6,4 mm)							
1/2	.875	22,2	3152	VPT 875	9	1.02	25,8
3/4	1.093-1.125	27,8-28,6	3032	VPT 1093	9	1.22	30,9
1	1.375	34,9	3036	VPT 1375	11	1.50	38,1
1-1/4	1.750	44,5	3038	VPT 1750	13	1.91	48,4
1-1/2	2.000	50,8	3158	VPT 2000	19	2.14	54,4
2	2.500	63,5	2793	VP 2.5	19	2.72	69,0

Standard color black. Consult Heyco for other colors.




Vent Plugs

Heyco® K. O. Filter Insert Vent Plugs

Polyurethane foam filters particle sizes 30 microns and larger

TRADE SIZE	MOUNTING HOLE DIAMETER		PART NO. Black	DESCRIPTION	PART DIMENSIONS		
	in.	mm.			No. of Vent Holes	Head Diameter	
					in.	mm.	
Multiple Locking Steps for Box Thickness up to .125" (3,2 mm)							
1/2	.875	22,2	4919	FIVP 875	9	1.02	25,8
3/4	1.093-1.125	27,8-28,6	4923	FIVP 1093	9	1.22	30,9
1	1.375	34,9	4931	FIVP 1375	11	1.50	38,1
1-1/4	1.750	44,5	*	FIVP 1750	13	1.91	48,4
1-1/2	2.000	50,8	4937	FIVP 2000	19	2.14	54,4
Multiple Locking Steps for Box Thickness up to .250" (6,4 mm)							
1/2	.875	22,2	4973	FIVPT 875	9	1.02	25,8
3/4	1.093-1.125	27,8-28,6	4977	FIVPT 1093	9	1.22	30,9
1	1.375	34,9	4983	FIVPT 1375	11	1.50	38,1
1-1/4	1.750	44,5	*	FIVPT 1750	13	1.91	48,4
1-1/2	2.000	50,8	4989	FIVPT 2000	19	2.14	54,4
2	2.500	63,5	4939	FIVP 2.5	19	2.72	69,0

Standard color black. *Consult Heyco for 1-1/4 KO part.



Louvered Plugs

Heyco® K. O. Louvered Plugs

TRADE SIZE	MOUNTING HOLE DIAMETER		PART NO. Black	DESCRIPTION	HEAD DIAMETER	
	in.	mm.			in.	mm.
Multiple Locking Steps for Box Thickness up to .125" (3,2 mm)						
1/2	.875	22,2	2557	LP 875	1.02	25,8
3/4	1.093-1.125	27,8-28,6	2561	LP 1093	1.22	30,9
1	1.375	34,9	2567	LP 1375	1.50	38,1
1-1/4	1.750	44,5	*	LP 1750	-	-
1-1/2	2.000	50,8	2594	LP 2000	2.17	55,1
Multiple Locking Steps for Box Thickness up to .250" (6,4 mm)						
2	2.500	63,5	2596	LP 2.5	2.72	69,0

Standard color black. *Consult Heyco for 1-1/4 KO part.

HEYClean™ K. O. Filter Insert Louvered Plugs

Polyurethane foam filters particle sizes 30 microns and larger

TRADE SIZE	MOUNTING HOLE DIAMETER		PART NO. Black	DESCRIPTION	HEAD DIAMETER	
	in.	mm.			in.	mm.
Multiple Locking Steps for Box Thickness up to .125" (3,2 mm)						
1/2	.875	22,2	4947	FILP 875	1.02	25,8
3/4	1.093-1.125	27,8-28,6	4951	FILP 1093	1.22	30,9
1	1.375	34,9	4957	FILP 1375	1.50	38,1
1-1/4	1.750	44,5	*	FILP 1750	-	-
1-1/2	2.000	50,8	4963	FILP 2000	2.17	55,1
Multiple Locking Steps for Box Thickness up to .250" (6,4 mm)						
2	2.500	63,5	4965	FILP 2.5	2.72	69,0

Standard color black. *Consult Heyco for 1-1/4 KO part.

Quick Specs

Material Certifications (VP only)

Flammability Rating Temperature Range

Nylon 6/6



Recognized under the Component Program of Underwriters' Laboratories, File E51579



Certified by Canadian Standards Association, File 8919

94V-2

-40°F (-40°C) to 221°F (105°C)