



Synthetic lock nuts with flange

Material: Polyamid PA 6
 Eigenschaften: halogenfrei
 Ausführung: 6-kant mit Flansch
 Einsatztemperatur: -30°C / +100°C

Material: Polyamide PA 6
 Properties: Halogen-free
 Execution: Hexagonal design with flange
 Temperature range: -30°C / +100°C

Synthetic Lock Nuts

Entry thread metric



Hellgrau RAL 7035			Light grey RAL 7035		
G	IC	M mm	Art.-Nr. Art. No.	📦	
M12x1.5	17	5.0	8255.12	100	
M16x1.5	22	5.0	8255.17	100	
M20x1.5	27	6.0	8255.20	100	
M25x1.5	33	6.7	8255.25	100	
M32x1.5	42	7.9	8255.32	50	
M40x1.5	48	8.4	8255.40	50	
M50x1.5	59	9.9	8255.50	10	
M63x1.5	73	11.0	8255.63	10	



Schwarz RAL 9005			Black RAL 9005		
G	IC	M mm	Art.-Nr. Art. No.	📦	
M12x1.5	17	5.0	8245.12	100	
M16x1.5	22	5.0	8245.17	100	
M20x1.5	27	6.0	8245.20	100	
M25x1.5	33	6.7	8245.25	100	
M32x1.5	42	7.9	8245.32	50	
M40x1.5	48	8.4	8245.40	50	
M50x1.5	59	9.9	8245.50	10	
M63x1.5	73	11.0	8245.63	10	

Synthetic Lock Nuts

Entry thread Pg



Hellgrau RAL 7035			Light grey RAL 7035		
G	IC	M mm	Art.-Nr. Art. No.	📦	
Pg 7	19	5.0	8255.07	100	
Pg 9	21	5.0	8255.09	100	
Pg 11	24	5.0	8255.11	100	
Pg 13	27	6.0	8255.13	100	
Pg 16	30	6.0	8255.16	100	
Pg 21	36	7.0	8255.21	50	
Pg 29	46	8.0	8255.29	50	
Pg 36	59	8.0	8255.36	25	
Pg 42	65	8.0	8255.42	10	
Pg 48	69	8.0	8255.48	10	



Schwarz RAL 9005			Black RAL 9005		
G	IC	M mm	Art.-Nr. Art. No.	📦	
Pg 7	19	5.0	8245.07	100	
Pg 9	21	5.0	8245.09	100	
Pg 11	24	5.0	8245.11	100	
Pg 13	27	6.0	8245.13	100	
Pg 16	30	6.0	8245.16	100	
Pg 21	36	7.0	8245.21	50	
Pg 29	46	8.0	8245.29	50	
Pg 36	59	8.0	8245.36	25	
Pg 42	65	8.0	8245.42	10	
Pg 48	69	8.0	8245.48	10	