

# Smooth Tubing



## SILICONE T117U

The SILICONE T117U tubing is an extruded unsupported tube made of silicone rubber.

It is highly well suited for harsh environments thanks to its excellent electrical and mechanical properties.

SILICONE T117U tubing is very flexible and fits perfectly over irregular shapes. It can be used for cable bundling and protection but it is also used for fluid transfer applications.

It is also flame retardant.

The SILICONE T117U tubing stands to very low temperatures (-55°C/-67°F) up to very high temperatures (200°C/392°F).

It is available in two wall thicknesses, depending on the required dielectric strength: .015" for 10kV and .035" for 15kV.

**Typical applications include:** coil and winding industry (coils, motors, generators, transformers...); lighting fixtures; recreational vehicles; technology, media and telecommunications; appliances; wind turbines and solar panels; heating and cooling; and in many other industrial fields.



## Characteristics & Properties

- **Colors:** standard colors are black, white, clear, red, yellow, blue and green. Other colors upon request.
- **Operating temperature:** -55°C / +200°C (-67°F / +392°F).
- **Flammability (UL 1441 VW-1):** pass.
- **Dielectric rating:** 300V for the .015" wall thickness and 600V for the .035" wall thickness.


## Dimensions

The following designation is for the .035" wall thickness version. Sizes for the .015" version are available from #24 thru #5. For the .015" designation, replace the 600 portion by 300.

Designation	NEMA sizes	Minimum Ø (inches)	Maximum Ø (inches)	Indicative nominal Ø	
				(inches)	(mm)
SILICONE T117U-600 AWG 24	24	0.020	0.027	0.024	0.61
SILICONE T117U-600 AWG 22	22	0.025	0.032	0.029	0.74
SILICONE T117U-600 AWG 20	20	0.032	0.039	0.036	0.91
SILICONE T117U-600 AWG 19	19	0.036	0.044	0.040	1.02
SILICONE T117U-600 AWG 18	18	0.040	0.049	0.045	1.14
SILICONE T117U-600 AWG 17	17	0.045	0.054	0.050	1.27
SILICONE T117U-600 AWG 16	16	0.051	0.061	0.056	1.42
SILICONE T117U-600 AWG 15	15	0.057	0.067	0.062	1.57
SILICONE T117U-600 AWG 14	14	0.064	0.074	0.069	1.75
SILICONE T117U-600 AWG 13	13	0.072	0.082	0.077	1.96
SILICONE T117U-600 AWG 12	12	0.081	0.091	0.086	2.18
SILICONE T117U-600 AWG 11	11	0.091	0.101	0.096	2.44
SILICONE T117U-600 AWG 10	10	0.102	0.112	0.107	2.72
SILICONE T117U-600 AWG 9	9	0.114	0.124	0.119	3.02
SILICONE T117U-600 AWG 8	8	0.129	0.141	0.135	3.43
SILICONE T117U-600 AWG 7	7	0.144	0.158	0.151	3.84
SILICONE T117U-600 AWG 6	6	0.162	0.178	0.170	4.32
SILICONE T117U-600 AWG 5	5	0.182	0.198	0.190	4.83
SILICONE T117U-600 AWG 4	4	0.204	0.224	0.214	5.44
SILICONE T117U-600 AWG 3	3	0.229	0.249	0.239	6.07
SILICONE T117U-600 AWG 2	2	0.258	0.278	0.268	6.81
SILICONE T117U-600 AWG 1	1	0.289	0.311	0.300	7.62
SILICONE T117U-600 5/16	5/16"	0.313	0.334	0.324	8.23
SILICONE T117U-600 AWG 0	0	0.325	0.347	0.336	8.53
SILICONE T117U-600 3/8	3/8"	0.375	0.399	0.387	9.83
SILICONE T117U-600 7/16	7/16"	0.438	0.462	0.450	11.43
SILICONE T117U-600 1/2	1/2"	0.500	0.524	0.512	13.00
SILICONE T117U-600 5/8	5/8"	0.625	0.655	0.640	16.26
SILICONE T117U-600 3/4	3/4"	0.750	0.786	0.768	19.51

## Packaging

SILICONE T117U tubing is delivered in rolls or in cut lengths.



Data and photos for information only. Delfingen makes no warranties as to the accuracy or completeness of this information. Delfingen reserves the right to make changes in materials or processing without notification.

Corporate Headquarters: DELFINGEN Industry S.A., Rue Emile Streit, 25340 Anteuil, France

Tel: +33 (0)3 81 90 73 00 • [delfingen@delfingen.com](mailto:delfingen@delfingen.com)

[www.delfingen.com](http://www.delfingen.com)