

## T120L9K2



**Article Number:** 111-12419

**Heavy Duty Cable Tie, 30" Long, 120lb Tensile Strength, PA66, Natural, 50/pkg**



Download spec sheet

### Base Data

**Local Order Number** T120L9K2

**Type** T120L

**Color** Natural (NA)

- Features and Benefits**
- Heavy duty design to offer higher tensile strength.
  - Head design provides high tensile strength with very low insertion force.
  - Bent tail ensures a quick and simple installation.

**Product Description** HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Fixation Method (FF)** None

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Heavy Duty Cable Tie, 30" Long, 120lb Tensile Strength, PA66, Natural, 50/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 120.0 lbs

**Minimum Tensile Strength (Metric)** 535.0 N

**Length L (Imperial)** 30.0 "

**Length L (Metric)** 760.0 mm

**Width W (Imperial)** 0.3 "

**Width W (Metric)** 7.6 mm

**Bundle Diameter Min. (Imperial)** 0.23 "

**Bundle Diameter Min. (Metric)** 5.76 mm

**Bundle Diameter Max. (Imperial)** 8.85 "

**Bundle Diameter Max. (Metric)** 225.0 mm

**Thickness T (Imperial)** 0.075 "

**Cable Tie Head Height (Metric)** 7.8 mm

**Cable Tie Head Length (Metric)** 10 mm

**Cable Tie Head Width (Metric)** 13 mm

**Cable Tie Head Length (Imperial)** 0.393 "

**Cable Tie Head Width (Imperial)** 0.502 "

Thickness T (Metric) 1.9 mm

## Logistics and Packaging

---

Quantity Per bag  
Package Quantity (Metric) 50  
Carton Quantity 1000  
Weight (Metric) 11.5 kg

## Material and Specifications

---

Material Polyamide 6.6 (PA66)  
Material Shortcut PA66  
US MILSPEC MS3367-6-9  
CSA Certified No  
Flammability UL94 V2  
Halogenfree Yes  
Operating Temperature -40°F to +185°F (-40°C to +85°C)  
ROHS compliant (Article 4 - 1) Yes  
Certification/Specification UL ZODZ2.E64139  
MIL 53421  
UL Listed (US and Canada) Yes  
UL Recognized (US and Canada) Yes