

## T120R9K2



**Article Number:** 112-12019

**Heavy Duty Cable Tie, 15.2" Long, 120lb Tensile Strength, PA66, Natural, 50/pkg**



Download drawing



Download spec sheet

### Base Data

**Local Order Number** T120R9K2

**Type** T120R

**Color** Natural (NA)

- Features and Benefits**
- Heavy duty design to offer higher tensile strength.
  - Head design provides high tensile strength with very low insertion force.
  - Bent tail ensures a quick and simple installation.

**Product Description** HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Fixation Method (FF)** None

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Heavy Duty Cable Tie, 15.2" Long, 120lb Tensile Strength, PA66, Natural, 50/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 120.0 lbs

**Minimum Tensile Strength (Metric)** 535.0 N

**Length L (Imperial)** 15.2 "

**Length L (Metric)** 387.0 mm

**Width W (Imperial)** 0.3 "

**Width W (Metric)** 7.6 mm

**Bundle Diameter Min. (Imperial)** 0.2 "

**Bundle Diameter Min. (Metric)** 5.0 mm

**Bundle Diameter Max. (Imperial)** 4.1 "

**Bundle Diameter Max. (Metric)** 105.0 mm

**Thickness T (Imperial)** 0.07 "

**Thickness T (Metric)** 1.8 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 50

**Carton Quantity** 1000

**Weight (Metric)** 5.14 kg

## Material and Specifications

---

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**US MILSPEC** MS3367-3-9

**CSA Certified** No

**Flammability** UL94 V2

**Halogenfree** Yes

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS compliant (Article 4 - 1)** Yes

**Certification/Specification** MS3367  
MIL 53421  
UL ZODZ2.E64139

**UL Listed (US and Canada)** Yes

**UL Recognized (US and Canada)** Yes