

## T150M0X2



**Article Number:** 111-00124

**Heavy Duty Cable Tie, 21" Long, 175 lb Tensile Strength, PA66, Black, 25/pkg**



Download spec sheet

### Base Data

**Local Order Number** T150M0X2

**Type** T150M

**Color** Black (BK)

**Features and Benefits**

- Heavy duty design to offer higher tensile strength.
- Head design provides high tensile strength with very low insertion force.

**Product Description** HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Fixation Method (FF)** None

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Heavy Duty Cable Tie, 21" Long, 175 lb Tensile Strength, PA66, Black, 25/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 175.0 lbs

**Minimum Tensile Strength (Metric)** 780.0 N

**Length L (Imperial)** 21.0 "

**Length L (Metric)** 530.0 mm

**Width W (Imperial)** 0.35 "

**Width W (Metric)** 8.9 mm

**Bundle Diameter Min. (Imperial)** 0.32 "

**Bundle Diameter Min. (Metric)** 8.0 mm

**Bundle Diameter Max. (Imperial)** 5.9 "

**Bundle Diameter Max. (Metric)** 150.0 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 25 Pieces

**Carton Quantity** 1000

### Material and Specifications

**Material** Polyamide 6.6 (PA66)

<b>Material Shortcut</b>	PA66
<b>CSA Certified</b>	No
<b>Flammability</b>	UL94 V2
<b>Halogenfree</b>	Yes
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS compliant (Article 4 - 1)</b>	Yes
<b>Certification/Specification</b>	UL ZODZ2.E64139
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	Yes