

## T150R9X2



**Article Number:** 111-15203

**Heavy Duty Cable Tie, 15.4" Long, 175 lb Tensile Strength, PA66, Natural, 25/pkg**



[Download drawing](#)



[Download spec sheet](#)

### Base Data

**Local Order Number** T150R9X2

**Type** T150R(U)

**Color** Natural (NA)

**Features and Benefits**

- Heavy duty design to offer higher tensile strength.
- Head design provides high tensile strength with very low insertion force.

**Product Description** HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Fixation Method (FF)** None

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Variant** Inside Serrated

**Short Description** Heavy Duty Cable Tie, 15.4" Long, 175 lb Tensile Strength, PA66, Natural, 25/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 175.0 lbs

**Minimum Tensile Strength (Metric)** 780.0 N

**Length L (Imperial)** 15.4 "

**Length L (Metric)** 390.0 mm

**Width W (Imperial)** 0.35 "

**Width W (Metric)** 8.8 mm

**Bundle Diameter Min. (Imperial)** 0.32 "

**Bundle Diameter Min. (Metric)** 8.0 mm

**Bundle Diameter Max. (Imperial)** 4.1 "

**Bundle Diameter Max. (Metric)** 105.0 mm

**Thickness T (Imperial)** 0.075 "

**Cable Tie Head Height (Metric)** 9.5 mm

**Cable Tie Head Length (Metric)** 14 mm

**Cable Tie Head Width (Metric)** 14 mm

**Cable Tie Head Length (Imperial)** 0.55 "

**Cable Tie Head Width (Imperial)** 0.55 "

**Thickness T (Metric)** 1.9 mm

### Logistics and Packaging

---

**Quantity Per** bag  
**Package Quantity (Metric)** 25  
**Carton Quantity** 1000

## Material and Specifications

---

**Material** Polyamide 6.6 (PA66)  
**Material Shortcut** PA66  
**CSA Certified** No  
**Flammability** UL94 V2  
**Halogenfree** Yes  
**Operating Temperature** -40°F to +185°F (-40°C to +85°C)  
**ROHS compliant (Article 4 - 1)** Yes  
**Certification/Specification** UL ZODZ2.E64139  
**UL Listed (US and Canada)** No  
**UL Recognized (US and Canada)** Yes