

## T150XL0X2



Article Number: 111-15500

Heavy Duty Cable Tie, 43.1" Long, 175 lb Tensile Strength, PA66, Black, 25/pkg



Download drawing



Download spec sheet

### Base Data

Local Order Number T150XL0X2

Type T150XL

Color Black (BK)

**Features and Benefits**

- Heavy duty design to offer higher tensile strength.
- Head design provides high tensile strength with very low insertion force.

**Product Description** HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Heavy Duty Cable Tie, 43.1" Long, 175 lb Tensile Strength, PA66, Black, 25/pkg

### Product Dimensions

Minimum Tensile Strength (Imperial) 175.0 lbs

Minimum Tensile Strength (Metric) 780.0 N

Length L (Imperial) 43.1 "

Length L (Metric) 1095.0 mm

Width W (Imperial) 0.35 "

Width W (Metric) 8.9 mm

Bundle Diameter Min. (Imperial) 6.0 "

Bundle Diameter Min. (Metric) 152.0 mm

Bundle Diameter Max. (Imperial) 13.0 "

Bundle Diameter Max. (Metric) 330.0 mm

Thickness T (Imperial) 0.083 "

Thickness T (Metric) 2.1 mm

### Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 25 Pieces

Carton Quantity 500

Weight (Metric) 20.8 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>CSA Certified</b>	No
<b>Flammability</b>	UL94 V2
<b>Halogenfree</b>	Yes
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS compliant (Article 4 - 1)</b>	Yes
<b>Certification/Specification</b>	UL ZODZ2.E64139
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	Yes