

111-01882

Article Number: 111-01882

Description: Standard Cable Tie, 4" Long, 18lb Tensile Strength, PA66, Red, 1000/pkg



| Base Data                           |   |
|-------------------------------------|---|
| Local Order Number                  | T18R2M4   |
| Type                                | T18R  |
| Color                               | Red (RD)  |
| Features and Benefits               | <ul style="list-style-type: none"> <li>• Inside serrations allow for strong hold on cables and wire bundles.</li> <li>• Head design provides high tensile strength with very low insertion force.</li> <li>• Bent tail ensures a quick and simple installation.</li> </ul>  |
| Quantity Per                        | bag   |
| Product Description                 | HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation. |
| Short Description                   | Standard Cable Tie, 4" Long, 18lb Tensile Strength, PA66, Red, 1000/pkg   |
| Product Dimensions                  |   |
| Minimum Tensile Strength (Imperial) | 18.0lbs   |
| Minimum Tensile Strength (Metric)   | 80.0N   |
| Length L (Imperial)                 | 4.0"  |
| Length L (Metric)                   | 100.0mm   |
| Fixation Method                     | None  |
| Identification Plate Position       | none  |
| Releasable Closure                  | No  |
| Tie Closure                         | plastic pawl  |
| Variant                             | Inside Serrated   |
| Width W (Imperial)                  | 0.1"  |
| Width W (Metric)                    | 2.45mm  |
| Bundle Diameter Min. (Imperial)     | 0.06"   |
| Bundle Diameter Min. (Metric)       | 1.5mm   |
| Bundle Diameter Max. (Imperial)     | 0.86"   |

111-01882



|                             |                               |                                  |
|-----------------------------|-------------------------------|----------------------------------|
| Product Dimensions          | Bundle Diameter Max. (Metric) | 22.0mm                           |
| Material and Specifications | Material                      | Polyamide 6.6 (PA66)             |
|                             | Material Shortcut             | PA66                             |
|                             | US MILSPEC                    | MS3367-4-2                       |
|                             | Flammability                  | UL94 V2                          |
|                             | Halogenfree                   | Yes                              |
|                             | Operating Temperature         | -40°F to +185°F (-40°C to +85°C) |
|                             | ROHS Compliant                | Yes                              |
|                             | Certification/Specification   | Cage Code 53421                  |
|                             | UL Listed (US and Canada)     | Yes                              |
|                             | UL Recognized (US and Canada) | Yes                              |
|                             | Logistic and Packaging        | Package Quantity (Metric)        |
| Customs Number(Schedule B)  |                               | 3926909987                       |