

## T18RA5000

Article Number: 120-05004

Cable Tie for AT2000, 18 lb Tensile Strength, PA66, Natural, 5,000/reel



Download spec sheet

### Base Data

<b>Local Order Number</b>	T18RA5000
<b>Type</b>	T18RA5000
<b>Color</b>	Natural (NA)
<b>Features and Benefits</b>	<ul style="list-style-type: none"><li>• The AT2000 cable tie system is designed for automatic installation on bundles up to .75" and a minimum tensile strength of 18 lbs.</li><li>• Available in reels of 5,000 each or bandoliers of 50 each.</li></ul>
<b>Product Description</b>	HellermannTyton offers the widest range of automatic cable tie tool systems which cover cable tie tensile strengths of 18, 30, and 50 pounds with bundle diameters between 1/16" to over 3". For use with HellermannTyton's Automatic Tool Systems.
<b>Power Supply unit</b>	Electrical
<b>Tie Closure</b>	plastic pawl
<b>Short Description</b>	Cable Tie for AT2000, 18 lb Tensile Strength, PA66, Natural, 5,000/reel

### Product Dimensions

<b>Minimum Tensile Strength (Imperial)</b>	18.0 lbs
<b>Minimum Tensile Strength (Metric)</b>	80.0 N
<b>Length L (Imperial)</b>	4.0 "
<b>Length L (Metric)</b>	4.8 mm
<b>Width W (Imperial)</b>	0.1 "
<b>Width W (Metric)</b>	2.5 mm
<b>Bundle Diameter Min. (Imperial)</b>	0.03 "
<b>Bundle Diameter Min. (Metric)</b>	0.7 mm
<b>Bundle Diameter Max. (Imperial)</b>	0.75 "
<b>Bundle Diameter Max. (Metric)</b>	20.0 mm

### Logistics and Packaging

<b>Quantity Per</b>	reel
<b>Package Quantity (Metric)</b>	5000
<b>Carton Quantity</b>	10000

### Material and Specifications

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>US MILSPEC</b>	MS3367-4-9

**Flammability** UL94 V2

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes